



Description:

Drill-Tec[™] Termination Bars are designed to terminate single-ply membranes at parapet walls and other penetrations. They are made of extruded aluminum with a mill finish or Series #304 stainless steel alloy, and have pre-punched holes spaced at 6" (152.4 mm) intervals on 10¹ (3.05 m) long bars. They are secured using Drill-Tec™ #14 Fasteners or Drill-Tec™ Masonry Anchors.

Products and Packaging:

Drill-Tec™ Flat Termination Bar #453D



- Material: 6063-T6 Extruded Aluminum
- **Dimensions:** .09" (2.28 mm) thick x 1" (25.4 mm) wide x 10' (3.05 m) length, per bar
- Holes: ¼" (6.35 mm) x 3/8" (9.53 mm) pre-punched holes on 6" (152.4 mm) o.c.
- Packaging: 50 bars x 10' (3.05 m) pc. per tube. 57 lb. (25.86 kg)

Drill-Tec™ Lip Termination Bar #453B



- Material: 6063-T6 Extruded Aluminum
- **Dimensions:** .09" (2.28 mm) thick x .75" (19 mm) wide x 10' (3.05 m) length per bar
- Holes: ¼" (6.35 mm) x 3/8" (9.53 mm) pre-punched holes on 6" (152.4 mm) o.c.
- Packaging: 50 bars x 10' (3.05 m) pc. per tube. 57 lb. (25.86 kg)

Drill-Tec™ Lip SE Termination Bar with Sealant Ledge #453WE



- Material: 6063-T6 Extruded Aluminum
- Dimensions: .075" (1.9 mm) thick x 1" (25.4 mm) wide x 10' (3.05 m) length per bar
- Holes: ¼" (6.35 mm) x 3/8" (9.53 mm) pre-punched holes on 6" (152.4 mm) o.c.
- Packaging: 50 bars x 10' (3.05 m) pc. per tube. 50 lb. (22.68 kg)

Drill-Tec™ Stainless Steel Flat Termination Bar #453DSS



- Material: 304 Stainless Steel
- Dimensions: .075 thick x 1" wide x 10' long per piece
- Holes: 1/4" x 3/8" slotted holes on 6" centers
- Packaging: 20 pieces per tube



32025 GAF • COMDT232-PDF-1125