



Description:

The GAF line of single-ply roofing systems includes a full line of sealants. GAF single-ply membrane sealants are specially formulated for TPO and PVC applications.

GAF Water Block

Uses:

A one-part, butyl-based, high-viscosity sealant suitable for sealing between flashing membrane and substrate surfaces, behind exposed termination bars, and between roofing membrane and drain flanges. Install only where it will be concealed from UV exposure, otherwise choose FlexSeal™ Caulk Sealant. GAF Water Block has been designed for use on all GAF EverGuard® TPO and PVC membranes.

Storage & Handling:

Keep material away from heat, sparks, and open flame. Store material in a clean and well-ventilated area at 40°F – 90°F (4.4°C – 32.2°C). Storage for continued periods outside this temperature range may shorten shelf life.

Shelf Life:

24 months from date of manufacture in unopened containers, assuming proper storage.

GAF Cut Edge Sealant

Uses:

Designed to seal the non-factory edges (cut edges) of the TPO membrane as a final step to reinforce membrane installation and inhibit water from traveling through the center scrim.

Coverage:

100 lineal ft. per pint (30 m per 473 ml) 1/8" (3 mm) bead when installed in accordance with GAF's application instructions.

Storage & Handling:

Store material in a clean and well-ventilated area at 40°F – 90°F (4°C – 32.2°C). Storage for continued periods outside this temperature range may shorten shelf life.

Shelf Life:

24 months from date of manufacture in unopened containers, assuming proper storage.



Visit [gaf.com](https://www.gaf.com)

For additional information, contact GAF Design Services at 1-877-423-7663 or designservices@gaf.com

We protect what matters most™

