



Description:

EverGuard™ EZ Fascia comprises a three-part assembly with a rigid formed retainer, decorative snap-on fascia cover, and matching splice plates for single-ply roofs. EverGuard™ EZ Fascia provides superior protection from wind and water penetration versus shop-fabricated roof edge.

Features and Benefits:

- Fast and easy installation, eliminating the need for "stripping in" that is typical of other roof edge designs.
- Retainers are self-locating with pre-punched slots to accommodate thermal expansion and contraction and reduce installation time.
- EverGuard[™] EZ Fascia includes 20 ga. galvanized steel retainers.
- Sizes range from 3.5 in. 9.25 in. (89 mm – 235 mm) face heights to accommodate multiple nailers and wall requirements.

- Covers can be manufactured in 22 ga. and 24 ga. galvanized steel (stainless steel available through custom order) or .040", and .050" aluminum.
- Factory-fabricated miters, scuppers, and drainage accessories provide a clean aesthetic and can help save time by eliminating the need for field fabrication.
- Express, standard, and premium colors and finishes are available to meet your job requirements, and include a 30-year limited Kynar 500® finish warranty on coil-coated standard colors. For limited warranty details, please visit gaf.com.
- Custom colors are also available. A 10-year limited warranty is included for post-painted Kynar®-coated aluminum applications unless otherwise stated. A 20-year limited warranty may be available upon request for certain colors.*

Product Specifications ■ 3 ½ in. (89 mm) ■ 7 ¾ in. (197 mm) Standard Sizes ■ 4 ¾ in. (121 mm) ■ 9 ¼ in. (235 mm) ■ 6 ¼ in. (159 mm) 12 ft. (6.10 m) Length ■ 22 ga. galvanized (stainless steel available through custom order) ■ .040" aluminum Materials ■ 24 ga. galvanized (stainless steel ■ .050" aluminum available through custom order) ■ Mill aluminum ■ Pre-finished anodized aluminum clear, bronze, or black ■ Pre-finished Kynar 500® ■ Post-finished anodized aluminum (See standard color chart) **Finishes** ■ Premium pre-finished Kynar 500® ■ Custom post-coated Kynar 500® (See standard color chart) finishes are available ■ Post-finished Kynar 500® 12 in. (305 mm) o.c. Pre-Punched Holes

Codes and Compliance:

- Tested in accordance with ANSI/SPRI /FM 4435/ES-1 Standard to comply with the International Building Code.
- FM-approved for winduplift protection. Refer to RoofNav.com for actual assemblies.



■ Miami-Dade Approved




10 Express Colors[†]

Express Colors are available for quick shipping to meet your job requirements.‡



For standard and premium colors, please refer to the GAF color chart, available at gaf.com/ perimeteredgemetal.

Custom colors are also available.



- * Restrictions apply; consult your GAF Territory Manager
- † Express Colors available in shorter lead times for 24 ga., .040", and .050" only. Standard lead times, which may be longer, apply for 22 ga.
- ‡ It is difficult to reproduce the color clarity of these products. Before selecting your color, please contact your local GAF territory manager to request a paint chip for accurate color representation.



Visit gaf.com

