

GAF

EverGuard®
Hercules® Drain



Description:

EverGuard® Hercules® Drains are part of the range of GAF roofing system accessories that provide roofing contractors with easy-to-install, factory-built details.

Application:

EverGuard® Hercules® Drains can be installed on any TPO, PVC, or asphaltic low-slope roofing system. See published application and specifications manual for detailed instructions.

Product Information:

The one-piece seamless body provides strength and durability without separation of the flange from the stem. The drain flange has a depressed sump area to improve flow and facilitate drainage. The retrofit drain is equipped with a heavy-duty cast aluminum strainer dome for strength and durability, and incorporates U-Flow® Seal technology, which helps provide a watertight mechanical connection to TPO or cast-iron pipes. Available in sizes compatible with 3" (76 mm), 4" (102 mm), 5" (127 mm), and 6" (152 mm) drain diameters.

- 0.125" (3.18 mm) 11 ga. spun aluminum
- 12" (305 mm) long drain stem designed to bypass the existing drain bowl to the water leader
- Incorporates U-Flow® Seal technology for a secure, watertight connection when properly installed
- Meets ANSI/SPRI RD1 standard for retrofit roof drains, which requires the seal to hold a 10 ft. column of water for 24 hours without leaking

Specifications				
Drain body	11 ga. 0.125" (3.18 mm) spun aluminum			
Flange	17.5" (445 mm) diameter with sump area			
Stem	12" (305 mm) length			
Shipping Specifications	3" (76 mm) compatible	4" (102 mm) compatible	5" (127 mm) compatible	6" (152 mm) compatible
Drain per carton	1			
Weight per box	7.4 lb. / 3.36 kg	7.9 lb. / 3.58 kg	7.9 lb. / 3.58 kg	8.5 lb. / 3.86 kg
Cartons per pallet	20			
Product SKUs				
	8523F	8523G	8523H	8523I



Visit [gaf.com](https://www.gaf.com)

For additional information, contact GAF Design Services at 1-877-423-7663 or designservices@gaf.com

We protect what matters most™

