



Description:

M-Bond™ Adhesive/Sealant is a moisture-curing polyether roofing sealant that bonds to asphaltic membranes, concrete, steel, aluminum, wood, glass, and PVC.

Uses:

Designed for use in the M-Curb™ Pitch Pocket System to seal around penetrations; also used to adhere the M-Curb™ Pitch Pocket System to the asphaltic roof. See M-Curb™ Pitch Pocket System Installation Instructions at gaf.com for more information.

Surface Preparation:

All surfaces shall be clean, sound, dry, and free of loose materials like rust, oil, wax, and grease. Wipe all new metal with rubbing alcohol before sealant application.

Shelf Life:

12 months from date of manufacture when stored at 70°F (21°C) with 50% relative humidity. High temperature and high relative humidity may significantly reduce shelf life. M-Bond™ Adhesive/Sealant will not freeze under normal conditions.

Packaging:

- 10.1 fl. oz. (300 ml)
- Color: Black

Precautions:

- Do not store in elevated temperatures. Elevated temperatures will reduce shelf life.
- Store unopened containers in a cool, dry area. Protect unopened containers from water, heat, and direct sunlight.
- Use only on clean, dry surfaces that are free of all surface contaminants.
- Do not apply in temperatures below 32°F (0°C).
- Do not cut or thin M-Bond™ Adhesive/Sealant.
- Cold temperatures and low humidity will slow curing.
- Do not use on TPO- or Kynar® PVDF-coated materials.
- Always test substrates to confirm adhesion.



Visit gaf.com

For additional information, contact GAF Design Services at 1-877-423-7663 or designservices@gaf.com

We protect what matters most™

