



## Description:

EverGuard® PVC 50 Mil Utility Flashing Membrane provides roofing contractors with an easy-to-install factory-built detail. It's constructed using GAF PVC with ELVALOY™, making it suitable for use with both EverGuard® PVC and EverGuard® PVC XK. This accessory is used to strip-in coated metal flanges at areas that require a reinforced membrane for flashing.

- Made with EverGuard® PVC KEE membrane for built-in reliability
- Factory-built accessories can help reduce risk of leaks and callbacks

## Application:

This detail can be installed on EverGuard® PVC and EverGuard® PVC XK 50-, 60-, and 80-mil mechanically attached, fully adhered, or RhinoBond® roofing systems. See published application and specifications manual for detailed instructions.

## Product Information:

50 Mil Flashing Membrane is manufactured with EverGuard® PVC KEE Membrane in accordance with strict GAF PVC specifications and designed for ease of installation. It can be used in a variety of flashing details, including stripping-in coated metal.

### SPECIFICATIONS

Roll size	8" x 100' (203 mm x 30.5 m) rolls
Material	50 mil reinforced PVC KEE membrane

### SHIPPING SPECIFICATIONS

Weight per roll	22 lb. (9.97 kg)
SKU	87B2920

*Note: ELVALOY™ is a trademark of The Dow Chemical Company.*



Visit [gaf.com](https://www.gaf.com)

For additional information, contact GAF Design Services at 1-877-423-7663 or [designservices@gaf.com](mailto:designservices@gaf.com)

We protect what matters most™

**GAF**