EverGuard and EverGuard Extreme TPO GAF Coated MetalSheets



Description:

Increase efficiency when creating edges, flashing, and other sheet metal details with EverGuard™ and EverGuard Extreme™ TPO-Coated Metal Sheets. This accessory cuts and forms like standard sheet metal. GAF manufactures these and other accessories from its proven, durable EverGuard® and EverGuard Extreme® membrane. GAF TPO accessories can help you reduce installation costs, risk of leaks, and callbacks, while helping you create a uniform look.

Application:

Use for metal gravel stop and drip edges, metal base and curb flashing, sealant pans, and scupper sleeves. Field and flashing TPO membrane heat welds directly to coated metal.

Product Information:

Metal sheets measure 4' (1.21 m) x 10' (3.05 m) and are constructed from 24 ga. steel with 25-mil EverGuard® or EverGuard Extreme® TPO membrane. Metal sheets are also available in .040 aluminum, 24 ga. stainless, and 20 ga. galvanized steel with a 2-4 week lead time.

TPO Coated Metal is available in white; colors available on request, minimum order requirements may apply. Please see the TPO Color Data Sheet for more details.

Specifications			
Size	4' (1.21 m) x 10' (3.05 m)		
Membrane thickness	0.025" (0.64 mm)		
Weight per sheet	40 lb. (18.14 kg)		
Shipping Specification	ns		
Sheets per pallet	5	10	30
EverGuard® TPO	760A	7600920	7603920
EverGuard Extreme® TPO	_	7600776	7603776



32025 GAF • COMEG852-PDF-1025