

# GAF Bulking Fiber

Coating Accessory



## Description:

GAF Bulking Fiber is a soft, flexible high-tensile polyethylene fiber used as a general thickener for GAF coatings.

## Uses:

GAF Bulking Fiber can be used to bulk up coatings to make them brushable mastics. Thicker materials allow for fabrication of cants and filling around irregular surfaces. Excellent for flashing details, inside and outside flashing details, round stacks, pipe legs, pitch pockets, conduit pipes, etc.

## Packaging Sizes:

- 15 lb. (6.8 L) bag

## Storage:

**Product Storage Temperature:**  
40°F - 70°F (4°C - 21°C).

Material must be dry before use.

## Physical Properties

Type	Test Values*
Melting Point	275°F (135°C)
Specific Gravity	0.965 g/cm <sup>3</sup>
Flash Point	665°F (352°C)
Moisture Content	<2.0%
Appearance	Fluffy fiber
Color	White

\* Values are approximate and subject to normal manufacturing variations. These values are not guaranteed and are provided solely as a guide.

## Application Instructions:

Apply evenly by trowel or brush. Total coverage is dependent on the substrate; rough or porous substrates may require additional product. If fabric-embedment is required, refer to Liquid-Applied Roofing Manual at [gaf.com](http://gaf.com). For application rates and other requirements for system guarantees and warranties, see Liquid-Applied Roofing Manual at [gaf.com](http://gaf.com).

## Mixing Instructions:

- **For Coatings:** Use hand tools to add GAF Bulking Fiber to coating at a ratio of 20% - 50% by volume.
- **For BarrierGuard®:** refer to the BarrierGuard® product data sheet.

## Limitations and Precautions:

Adding GAF Bulking Fiber to silicone coating will shorten pot life. DO NOT add more than one hour in advance. DO NOT mix more material than will be used during one working period. DO NOT allow moisture content within bag.

## Safety and Handling:

For specific information regarding safe handling of this material, please refer to the Safety Data Sheet (SDS).

## Cleanup:

Sweep or vacuum loose fibers. Thoroughly rinse application equipment with water.

## Warranty:

Refer to applicable warranties and guarantees, available at [gaf.com](http://gaf.com), for complete coverage and restrictions.



Visit [gaf.com](http://gaf.com)

For additional information, contact GAF Design Services at 1-877-423-7663 or [designservices@gaf.com](mailto:designservices@gaf.com)

We protect what matters most™

