


# GAF PMMA Catalyst Powder



## **GAF** PMMA Catalyst Resin Curing Agent – Powder

ITEM CODE: 8186



### Description:

GAF PMMA Catalyst Powder, a reactive agent used to induce curing of GAF PMMA Flashing Resin, is supplied as a white granular powder in pre-measured packets. GAF PMMA Catalyst Powder is to be mixed with GAF PMMA Resin, Paste, and Primer.

### Application:

- Refer to applicable GAF Installation Guide and GAF PMMA Flashing Resin Data Sheets for detailed application information, including mixing ratios for specific products.

### Storage and Handling:

- For specific information regarding safe handling of this material, please refer to the appropriate Safety Data Sheet (SDS).
- GAF PMMA Catalyst Powder should be stored in its box at all times until just prior to use.
- Always store in a cool and dry location. Do not store in direct sunlight or in temperatures below 32°F (0°C) or above 77°F (25°C).
- Materials stored on the project site during application should be kept on a pallet in a shaded, well-ventilated area. In unshaded areas, materials should be covered with a white, reflective tarp in a manner that allows for air circulation beneath the tarp.

### Precautions:

- GAF PMMA Catalyst Powder is stable if stored and used in accordance with GAF guidelines.
- GAF PMMA Catalyst Powder is heat sensitive and should be stored under controlled conditions to ensure that the reactivity/effectiveness is not compromised as well as for safety reasons.
- GAF PMMA Catalyst Powder should not be exposed to temperatures in excess of 122°F (50°C). Product exposed to temperatures in excess of 122°F (50°C) may experience hazardous self-accelerating decomposition. Self-accelerated decomposition is signaled by the presence of bright white smoke and the process can generate high temperatures, depending on the environmental conditions and quantity of product.
- Shelf life: 6 months from date of manufacture.

### Physical Properties:

Application Temperature (Air)*	59°F – 104°F (15°C – 40°C)
Application Temperature (Surface)*	50°F – 122°F (10°C – 50°C)
Color	White

\* Reference PMMA Installation Guide for application temperatures

### Packaging:

- GAF PMMA Catalyst Powder is available in a specially designed vented box containing 10 pre-measured 0.1 kg (100 g) (3.2 oz) plastic bags (1 kg total). A 1-tablespoon measuring scoop is included in each box.
- For application questions contact GAF Technical Services at 1-800-766-3411 or visit [gaf.com](http://gaf.com).



Visit [gaf.com](http://gaf.com)

For additional information, contact GAF Design Services at **1-877-423-7663** or [designservices@gaf.com](mailto:designservices@gaf.com)

We protect what matters most™

