



GAF PMMA Cleaner Clear Blended Solvent

ITEM CODE: 8185



Description:

GAF PMMA Cleaner is a clear blended solvent used for preparing the substrate to receive GAF PMMA Flashing.

Advantages:

- Ideal for use on asphaltic BUR (with SBS Cap Target Patch) and SBS-modified bitumen substrates and PVC or PVC KEE membranes
- Specially made for use with GAF PMMA Flashing System
- Can be applied by brush, rag, or cloth

Application:

Substrate Preparation — Substrate must be clean, completely dry, and free from any foreign matter. Pressure-wash to remove all dust and debris, and allow to dry. Check for any damaged roof membranes, including all flashings and penetrations, and repair before coating.

Mixing — GAF PMMA Cleaner is a ready-to-use material; however, some settling of material may occur during shipment and storage. Mix prior to use.

Application — GAF PMMA Cleaner may be applied by rag or cloth. Use only butyl rubber or nitrile gloves when mixing. Apply evenly at a rate of 0.2 gal/100 ft² (0.8 L/10 m²) per coat.

Pot Life & Drying Time — GAF PMMA Cleaner requires approximately 20 minutes drying time.



Visit [gaf.com](https://www.gaf.com)

For additional information, contact GAF Design Services at 1-877-423-7663 or designservices@gaf.com

Coverage — Consumption will vary depending upon application and use.

Disposal — GAF PMMA Cleaner is considered a hazardous material and must be handled as such, in accordance with local, state, and federal regulations. Refer to the GAF PMMA Cleaner Safety Data Sheet (SDS) and the GAF PMMA Flashing System Guide for additional information, and prior to handling or use.

Refer to GAF PMMA Flashing System Guide for application information.

For application questions — Contact GAF Technical Services at 1-800-766-3411 or visit [gaf.com](https://www.gaf.com).

Limitations & Precautions:

IMPORTANT: Repair leaks promptly to avoid adverse effects, including mold growth.

- Do NOT apply on wet substrates.
- Do NOT heat container.
- Do NOT attempt to thin product.
- Do NOT apply if rain, dew, fog, heavy moisture condensation, or freezing temperatures are in the 24-hour forecast.
- Use butyl rubber or nitrile gloves when handling.

Safety & Handling:

For specific information regarding safe handling of this material, please refer to the Safety Data Sheet (SDS).

Physical Properties:

Unit of Measure	1 Gal (3.8 L)
Application Temperature (Air)	50°F (10°C) and rising (15°C - 40°C)
Application Temperature (Surface)	50°F - 110°F (10°C - 43°C)
Color	Clear
Drying Time	20 minutes

Packaging & Shelf Life:

- GAF PMMA Cleaner is supplied in a 1-gallon (3.8 L) can.
- Shelf life 12 months if stored properly in a clean and well-ventilated area at 50°F - 90°F (10°C - 32°C). Storage for continued periods outside this temperature range may shorten shelf life. Keep containers covered when not in use.
- DO NOT allow cleaner to freeze and store in a cool, dry environment at temperatures between 55°F - 80°F.

