



GAF PMMA Fleece Polyester Fabric



Description:

GAF PMMA Fleece is a non-woven, needle-punched polyester fabric reinforcement specially designed for use with the GAF PMMA Flashing System.

Advantages:

- 100% polyester reinforcement for penetrations
- Easily conforms around complex penetrations
- Polyester reinforced fabric improves strength while maintaining flexibility
- Good for use in smoothing and repairing "alligatored" asphaltic membranes
- Quick saturation for strong reinforcing bond between layers
- Helps maintain membrane uniformity

Basic Uses:

GAF PMMA Fleece is designed to reinforce areas of PVC, PVC KEE, BUR (With SBS Cap Target Patch), and SBS. Asphaltic substrates that are heavily alligatored or contain numerous cracks, seams, joints, or splits should be addressed with GAF PMMA Resin.

Application:

Substrate Preparation — As a minimum, clean and prepare existing surfaces to receive GAF PMMA Fleece by removing all loose and flaking particles, grease, and laitance with the use of a stiff-bristle push broom and/or washing. Care should be taken not to inject water into the substrate during washing. In some cases, additional drying time may be required after the cleaning process.

Application — GAF PMMA Fleece should be installed as required after application of any primers or caulk, and prior to application of the coating on the field of the roof. Cut the fabric to the desired length. Slit the bottom half of fabric used around vent pipes and other circular protrusions so that it lies flat. Immediately embed fabric into wet coating and work it with a brush so that it is saturated with coating. All reinforcement fabric shall be 100% adhered to the substrate, with no tenting or air pockets.

GAF PMMA Fleece should be embedded into GAF PMMA Flashing Resin – Summer or Winter Grade. See GAF PMMA Flashing System Guide for details.

Physical Properties:

Weight	110 g/m ²
Color	White
Water Absorption	<1.0%
Thickness	40 mils

Storage and Handling:

GAF PMMA Fleece should be stored in an upright position on a dry, clean flat surface. Store in a dry place on an elevated pallet out of direct exposure to the elements and should not be stacked. There is no shelf-life limitation with proper storage. See product packaging and Safety data Sheet (SDS) for specific information on the safe handling of this product.

Packaging:

Roll Size	Code
1 ft. (305 mm) x 82 ft (25 m)	89119900
1 ft. (305 mm) x 164 ft (50 m)	89117900
3.4 ft. (1.04 m) x 164 ft (50 m)	89117000
2.1 ft. (655 mm) x 164 ft (50 m)	89117700

Shelf life indefinite if stored properly in a cool and dry location. Store roll in an upright position to avoid deforming rolls and creasing fabric.



Visit gaf.com

For additional information, contact GAF Design Services at **1-877-423-7663** or designservices@gaf.com

We protect what matters most™

