

LIBERTY™ Self-Adhering Cap Sheet

An SBS-modified, granule-surfaced roofing membrane provides durable protection for residential low-slope areas



- Perfect for low-slope roofs such as on porches, garages, carports, and sheds
- Self-adhering installation eliminates the need for open flames, hot asphalt, or dangerous chemicals on your roof
- Nine popular colors help complement Timberline® and other GAF asphalt shingle colors

LIBERTY™ Self-Adhering Cap Sheet



Description:

LIBERTY™ Self-Adhering Cap Sheet is a durable SBS-modified bitumen, granule-surfaced membrane designed and manufactured to meet relevant industry and code requirements. We reinforced this waterproofing membrane with a polyester mat coated with polymer-modified asphalt.

Advantages:

- **LIBERTY™ systems are applied** without torches, open flames, or hot asphalt, and are suitable for primed plywood decks and other substrates.
- **Available in nine popular colors** to help complement Timberline® and other GAF asphalt shingle colors. (Barkwood, Black, Hickory, Pewter Gray, Shakeswood, Slate, Tan, Weathered Wood, and White)
- **Up to 20-Year Limited Warranty** against manufacturing defects available, depending on systems.*

This product meets or exceeds the following ASTM D6164 Type I, Grade G minimum requirements:

Properties	Test Method	Value
Tensile strength @ 0°F (min.), lbf/in.	ASTM D5147	70
Elongation @ 0°F (nom.), %	ASTM D5147	20
Low-temperature flexibility (max.), °F	ASTM D5147	0
Tear strength (min.), lbf	ASTM D5147	55
Dimensional stability, (max.) %	ASTM D5147	1

Note: Values stated are approximate and subject to normal manufacturing variation. These values are not guaranteed and are provided solely as a guide. GAF reserves the right to change or modify, at its discretion, any of the information, requirements, specifications, or policies contained in this document.

Uses:

LIBERTY™ Self-Adhering Base/Ply Sheet is designed for use with LIBERTY™ Self-Adhering Cap Sheet to help protect the low-slope areas ($\frac{1}{4}$:12 – 3:12)⁴ of your roof such as porches, garages, carports, and sheds.

Paired with the Cap Sheet, the complete, 2-Ply LIBERTY™ System passes UL 2218A Class 4 Impact Testing.

Application:

LIBERTY™ Self-Adhering Cap Sheet is applied to approved substrates using its unique self-adhering formulation. Technical and sales information can be obtained through Technical Services at 877-GAF-ROOF.

Application Standards:

- **UL Classified to ANSI/UL790¹, Class C Roofing Fire Rating**
- **Miami-Dade County Product Control Approved**
- **State of Florida Approved**
- **Meets or Exceeds the Requirements of the Texas Department of Insurance**
- **ASTM D6164 Type I, Grade G**
- **UL Evaluation Report UL ER1306-02**
- **Passes UL 2218A Class 4 Impact Testing when paired with the LIBERTY™ Base/Ply Sheet⁵**

Product details:

Roll size	1 square — excludes laps ² 111.6 gross sq. ft. (10.4 m ²)
Roll length	34.0' (10.4 m)
Roll width	39.375" (1.0 m)
Aprox. roll weight	96.4 lb. (43.7 kg)
Product thickness	0.157" (4 mm)

* Exclusions apply. See *Limited Warranty on LIBERTY™ SBS Self-Adhering Materials* for complete coverage and restrictions.

¹ Refer to UL Product iQ for actual assemblies.

² Installed coverage will be lower and depend on quantity and width of side and end laps.

³ Meets certain FORTIFIED Roof™ requirements. Visit gaf.com/Fortified and current FORTIFIED Home™ Standard available at fortifiedhome.org for details. U.S. only.

⁴ LIBERTY™ SBS Self-Adhering Roof System may be appropriate for roof sizes at or below 2,500 square feet.

⁵ UL 2218A Class 4 Impact Resistance refers to complete 2-ply LIBERTY™ SBS Self-Adhering Roofing System.

For more information, please visit gaf.com/Liberty.
For questions on application, call GAF at **877-GAF ROOF**.



We protect what matters most™

