



Description:

M-Thane™ Two-Part Pourable Sealant is a self-leveling, two-component urethane rubber sealant. When Part A and Part B are mixed properly, M-Thane™ Two-Part Pourable Sealant cures as a tough, waterproof rubber with excellent adhesion to asphaltic membranes, concrete, steel, aluminum, wood, glass, and PVC.

Uses:

Designed for use in the M-Curb™ Pitch Pocket System to fill the pocket with waterproofing sealant. See M-Curb™ Pitch Pocket System Installation Instructions at gaf.com for more information.

Advantages:

- Unlimited cure depth
- Sets up quickly
- Self-leveling — fills and penetrates cracks with tough urethane rubber

Mixing Instructions:

For best results, maintain this product at room temperature 24 hours before mixing. Pour all of M-Thane™ Two-Part Pourable Sealant Part B into Part A container and mix for 3 – 5 minutes with mixing paddle and drill. Mixed product must be a uniform black color with no streaks or unmixed resin. Do not mix partial quantities. Do not attempt to thin with solvent or add foreign substances.

Shelf Life:

12 months from date of manufacture.

Packaging:

- 2 gallons (8 liters), with 2 containers each of Activator and of Mixing Blade.
- Color: Black

Precautions:

- Do not apply in temperatures below 40°F (4.4°C).
- Do not apply if rain is anticipated within 4 hours.
- Do not use in areas subject to continuous immersion.
- Do not prime bonding surfaces with asphalt primer.
- Do not use petroleum-based solvents such as mineral spirits or xylene for cleaning purposes.
- Smooth APP membranes require a prior installation of a granulated target of APP-modified bitumen around the penetration.
- Test and evaluate to ensure adequate adhesion.
- Store unopened containers in a cool, dry place. Protect opened containers from water, heat, and direct sunlight.

Typical Properties

Density Part A (lb./gal)	0.994 g/mL
Density Part B (lb./gal)	0.110 g/mL
Tensile Strength	126 psi
Elongation @ Break	97%



Visit gaf.com

For additional information, contact GAF Design Services at 1-877-423-7663 or designservices@gaf.com

We protect what matters most™

