GAF Steely™ Drain

Retro Fit Deck Drain

Description:

GAF Steely™ Drain is part of the range of GAF single-ply roofing system accessories that provide contractors with easy-to-install, factory-built details. It features a laser-etched QR Code that allows you to enter installer/design professional information, system information, and maintenance records.*

- Helps eliminate the need for core cuts to identify system components — just scan the QR code to access a list of the system components
- Made of 316L Marine-Grade Stainless Steel, which is suitable for harsh environments, helps to reduce drain water odors, and provides high resistance to heat
- Key hole features for easy installation and removal: simply twist the dome — no need to remove nuts

Application:

GAF Steely™ Drain can be installed using conventional techniques for either new or retrofit drain applications on mechanically attached, adhered, and induction-welded TPO roofing and PVC systems. See published application and specifications manual for detailed instructions at gaf.com.

To register your drain:

1) Scan the QR code with a GPS-enabled phone or tablet
2) Follow the link (and allow location permissions to the website)
3) Fill in your Roof Specs and click "Register."

Product Information:

- Deck (.050″) and Stem (.040″) made of high-strength 316L Stainless Steel providing maximum corrosion resistance
- Flange designed for optimum seal with roof flashing
- Drain Kit contains heavy-duty formed stainless-steel dome with 33 drainage slots, flange/clamping ring, flow control, and drain seal
- Meets ANSI/SPRI RD1 for back flow prevention for improved flow performance

Specifications				
Drain body (deck)	.050″ 316L Formed Stainless Steel			
Flange width (deck)	18″ (457 mm)			
Stem (tube) length	11.3″ (287 mm)			
Drain size (tube) dimensions	3″ (76 mm)	4″ (102 mm)	5″ (127 mm)	6″ (152 mm)
Tube (outside diameter)	2.80″ (71 mm)	3.80″ (97 mm)	4.80″ (122 mm)	5.80″ (147 mm)
Shipping Specifications				
Drains per carton	1			
Weight per carton	13.2 lb. (5.99 kg)	13.7 lb. (6.21 kg)	14.1 lb. (6.40 kg)	14.6 lb. (6.62 kg)
Cartons per pallet	20			
Item #	8523SD003	8523SD004	8523SD005	8523SD006

The Steely™ Drain flow control will perform as a drain restricter with the following flow rate:

Water head level	Gallons per minute
Under a 4″ head of water	30
Under a 3″ head of water	20
Under a 2″ head of water	12
Under a 1″ head of water	8

* For information on how GAF processes your information, please review the GAF Privacy Policy.

Visit **gaf.com**

For additional information, contact GAF Design Services at **1-877-423-7663** or **designservices@gaf.com**

We protect what matters most™

©2025 GAF • COMGN892-PDF-0525