



#### **GRT Fastening Kit - Screw & Washer**

Three wooden deck tiles are placed on a pedestal. The screw and washer is placed into the fastening slot of each wood deck tile. The fourth deck tile is placed on the pedestal and the screw is fastened down to lock the wood deck tiles in place.

#### **GRT Fastening Kit - Plastic Pin**

Align the holes on the underside of the wood deck tiles with the plastic pins in the pedestals. Push down on the tiles until connection is complete.

#### **Notes:**

1. Installation to be completed in accordance with manufacturer's specifications.
2. This drawing is intended for use contractors, engineers, consultants, and design professional for planning purposes only. This drawing may not be used for construction.
3. All information contained herein was current at the time of development but must be reviewed and approved by the product manufacturer to be considered accurate.
4. For additional information on installation of the roof assembly, refer to the applicable GAF system details and manual.
5. Visit [www.GreenriseTech.com](http://www.GreenriseTech.com) for additional product and company information.

## GRT Wood Deck Tile Fastening Kits

Roof Area:  
Field of Roof

Issue Date:  
1/18/2024

Scale:  
N.T.S.

Detail No:

**121**