



NOTE:

- 1. REFERENCE SPECIFIC SYSTEM/INSULATION TYPE AND THICKNESS REQUIREMENTS.
  - 2. DRILL-TEC™ RHINO BOND® ATTACHMENT SYSTEM IS NOT ACCEPTABLE FOR GYPSUM, CEMENTITIOUS WOOD FIBER OR OSB.
  - 3. REFER TO THE RHINO BOND® SPEC MANUAL FOR FASTENER AND DECK REQUIREMENTS.
  - 4. CONSULT FM APPROVALS, ROOFNAV LISTINGS, AND FM DATA SHEETS 1-28 AND 1-29 AT [HTTP://ROOFNAV.COM](http://ROOFNAV.COM), FOR DETAILED INSTALLATION REQUIREMENTS AND RECOMMENDATIONS FOR FM APPROVED INSTALLATIONS OR CONTACT TECHNICAL SALES SUPPORT AT 800-766-3411 FOR ASSISTANCE.
- \*THE FIELD OF ROOF ATTACHMENTS ABOVE EQUATE TO FM 1-120 RATINGS



120 PSF FASTENING PATTERN  
- OVER APPROVED STEEL AND CONCRETE DECKS

DRAWING #	THIS DETAIL APPLIES TO:		ISSUE / REVISION DATE	SCALE
122	RHINO BOND® SYSTEMS		8/17/20	N.T.S.

LEGEND

● ● ● FASTENERS