## SINGLE-PLY: TPO & PVC FASTEN SCUPPER MEMBRANE ON FRONT SIDE OF PARAPET FRONT SIDE OF PARAPET WALL WALL WITH EVERGUARD® TERMINATION BAR (OPTIONAL) -EVERGUARD® COATED METAL WITH HEMMED EDGE -DRILL-TEC<sup>™</sup> FASTENERS 12" (305 mm) O.C (MIN. 1 PER PLANE) 0 PREMANUFACTURED OR UNREINFORCED REFER TO FIELD FABRICATED CORNERS PARAPET AND - HEAT WELDED WALL DETAIL FOR **TERMINATION** DRILL-TEC<sup>™</sup> PLATES & FASTENERS 12" (305 mm) O.C. (6" [152 mm] O.C. FOR BALLASTED SYSTEMS) REINFORCED EVERGUARD® MEMBRANE (PERIMETER SHEET IF REQUIRED) MULTIPLE LAYERS OF ENERGYGUARD™ ROOF **INSULATION** ROOF DECK/SUBSTRATE

NOTE:

1. DETAIL TO BE USED IN CONJUNCTION WITH STANDARD GUIDE SPECIFICATION CONTAINING REQUIREMENTS FOR NAILERS, INSULATION ETC.

WOOD NAILER, 2" (50.8 mm) x 4" (102 mm) MIN.

WIDE SECURED TO DECK (OPTIONAL)

2. FOR INSULATION THICKNESS GREATER THAN 8" (203 mm), A COVER BOARD IS REQUIRED ON MECHANICALLY ATTACHED SYSTEMS ONLY.

	SCUPPER - FIELD FABRICATED				LEGEND	
GAF	OPEN TOP					
	DRAWING #		THIS DETAIL APPLIES TO:	ISSUE / REVISION DATE	SCALE	######################################
	322		ALL SYSTEMS	8/24/20	N.T.S.	