



NOTES:

1. APPROVED FOR USE OVER ANY RUBEROID® GRANULE SBS (COLD-ADHESIVE APPLIED).
2. REFER TO THE GAF PMMA FLASHING INSTALLATION INSTRUCTIONS FOR PROPER SURFACE TREATMENT OF ALL MATERIALS.
3. REFER TO GAF DETAILS 075600-901 & 075600-902 FOR GAF PMMA FLEECE CONFIGURATIONS, CUTTING, FOLDING, & LAPPING TECHNIQUES.
4. PMMA FLASHING IS COVERED UNDER THE APPLICABLE SYSTEM WARRANTY.
5. BEFORE APPLICATION OF GAF PMMA FLASHING, GAF PMMA PASTE OR FLEXSEAL CAULK GRADE SEALANT SHOULD BE USED TO FILL VOIDS WHERE ROOFING MEMBRANES TERMINATE AT PENETRATIONS.

Irregular Penetration Flashing



We
protect
what
matters
most™

Legend:

Sealant



Product:

GAF PMMA
Flashing

Installation

Method:
Over
Cold-Adhesive
Applied SBS

Maximum

Warranty:
See Note #4

Date:

12/19/2024

Scale:

Not To Scale

Detail No.

075600

334