



#### NOTES:

1. CLEAN METAL AND MEMBRANE WITH EVERGUARD® TPO SEAM CLEANER AND ALLOW TO DRY.
2. EDGE METAL SHOULD BE DESIGNED FOR WIND RESISTANCE IN ACCORDANCE WITH THE APPLICABLE EDITION OF ASCE 7 AND TESTED FOR CAPACITY IN ACCORDANCE WITH THE TEST METHODS IN THE APPLICABLE EDITION OF ANSI/SPRI ES-1.
3. NOT FOR USE ON SLOPES GREATER THAN 3:12.
4. NOT RECOMMENDED FOR ROOFS LIKELY TO EXPERIENCE SUBSTANTIAL SNOW AND ICE ACCUMULATION IN PROXIMITY TO THE GUTTER/EDGE.
5. IN DRY REGIONS WHERE CUT EDGE SEALANT IS NOT AVAILABLE, FLEXSEAL™ CAULK-GRADE SEALANT IS AN ACCEPTABLE ALTERNATIVE.

## Primerless Cover Tape Overlap at Edge Metal Corner



We  
protect  
what  
matters  
most™

#### Legend:

Sealant



#### Product:

EverGuard TPO  
Primerless  
Cover Tape

#### Installation:

Over TPO Only

#### Maximum Warranty:

20 Years

#### Date:

8/5/2025

#### Scale:

3" = 1'

#### Detail No.

075423

**224**