



NOTES:

1. CLEAN METAL AND MEMBRANE WITH EVERGUARD® TPO SEAM CLEANER AND ALLOW TO DRY.
2. EDGE METAL SHOULD BE DESIGNED FOR WIND RESISTANCE IN ACCORDANCE WITH THE APPLICABLE EDITION OF ASCE 7 AND TESTED FOR CAPACITY IN ACCORDANCE WITH THE TEST METHODS IN THE APPLICABLE EDITION OF ANSI/SPRI ES-1.
3. NOT FOR USE ON SLOPES GREATER THAN 3:12.
4. NOT RECOMMENDED FOR ROOFS LIKELY TO EXPERIENCE SUBSTANTIAL SNOW AND ICE ACCUMULATION IN PROXIMITY TO THE GUTTER/EDGE.
5. IN DRY REGIONS WHERE CUT EDGE SEALANT IS NOT AVAILABLE, FLEXSEAL™ CAULK-GRADE SEALANT IS AN ACCEPTABLE ALTERNATIVE.

Primerless Cover Tape Overlap at Edge Metal



We
protect
what
matters
most™

Legend:

Sealant



Product:
EverGuard TPO
Primerless
Cover Tape

Installation:
Over TPO Only

**Maximum
Warranty:**
20 Years

Date:
8/5/2025

Scale:
3" = 1'

Detail No.
075423

223