



NOTES:

1. FOR HEAT-WELDED LAPS, USE A 1-1/2" [38 mm] WIDE WELD WITH A MACHINE AUTOMATIC WELDER OR A 2" [51 mm] WIDE WELD WHEN USING A HAND WELDER.
2. EDGE METAL SHOULD BE DESIGNED FOR WIND RESISTANCE IN ACCORDANCE WITH THE APPLICABLE EDITION OF ASCE 7 AND TESTED FOR CAPACITY IN ACCORDANCE WITH THE TEST METHODS IN THE APPLICABLE EDITION OF ANSI/SPRI ES-1.
3. EVERGUARD® TPO ACCESSORIES ARE ELIGIBLE FOR GUARANTEES UP TO 20 YEARS. EVERGUARD EXTREME® TPO ACCESSORIES ARE REQUIRED FOR GUARANTEES 25 YEARS AND UP.
4. REQUIREMENTS AND RECOMMENDATIONS OUTLINED IN THE APPLICABLE GAF MANUAL OR GUIDE SHALL APPLY IN ADDITION TO THE DRAWING ABOVE.

Coated Edge Metal with Heat-welded Flashing Strip



**We
protect
what
matters
most™**

Legend:

Heat Weld



Adhesive



Product:

EverGuard TPO
Fleece-back

Installation

Method:

Hybrid

Maximum

Warranty:

35 Years

Date:

7/11/2025

Scale:

3" = 1'

Detail No.

07 54 23

921