

NIOTEC:

- SCUPPER CAN ALSO BE FABRICATED PER SMACNA GUIDELINES USING EVERGUARD™ TPO COATED METAL, UNREINFORCED EVERGUARD® SMOOTH MEMBRANE, AND EVERGUARD™ TPO FLASHING ACCESSORIES.
- 2. FOR 25 YEAR GUARANTEES AND UP, EVERGUARD EXTREME® TPO PRODUCTS MUST BE USED.
- 3. REINFORCEMENT IS INCLUDED IN PREMANUFACTURED SCUPPERS. FOR FIELD-FABRICATED SCUPPERS, ENSURE ALL (4) ROOF-SIDE CORNERS OF THE SCUPPER ARE COMPLETELY SEALED USING EVERGUARD® UNREINFORCED DETAILING MEMBRANE OR EVERGUARD® PREFORMED CORNER ACCESSORIES.
- 4. REQUIREMENTS AND RECOMMENDATIONS OUTLINED IN THE APPLICABLE GAF MANUAL OR GUIDE SHALL APPLY IN ADDITION TO THE DRAWING ABOVE.

## **TPO Scupper Installation - Overflow**



We protect what matters most™

Legend: Heat Weld

Sealant

Adhesive .....

Product:

EverGuard TPO Fleece-back

**Installation:** Hybrid

Maximum Warranty: 35 Years

**Date:** 8/5/2025

**Scale:** 3" = 1'

**Detail No.** 07 54 23