



RoofCoatings

Premium Acrylic HydroStop® Installation Checklist (Non-metal applications)



Prep Substrate

- ☐ GAF Cleaning Concentrate
- ☐ Power washer
- ☐ Blower
- ☐ Squeegee/broom

Prime (where required)

- ☐ Primer
- ☐ Extension cord
- ☐ ½" drill (for mixer)
- ☐ Paddle mixer/mixing stick

Flashing Details (GAF Premium Brush-Grade Acrylic Flashing)

Check with GAF Technical Sales Rep for specific seam treatment instructions.

- ☐ Pails
- ☐ Roofing shears
- ☐ 12" Premium GAF Fabric
- ☐ 4" Hand roof brush or chip brush



Base Coat (GAF Premium Acrylic HydroStop® Base Coat & Fabric)

- ☐ 40" Premium GAF Fabric
- ☐ 10" Roof block brush
- ☐ Tapered brush handle

GAF Premium Acrylic HydroStop® Top Coat

- ☐ Wet mil gauge
- ☐ ½" drill (for mixer)
- ☐ Paddle mixer
- ☐ 2 extendable poles
- ☐ 9" or 18" heavy-duty roller frames
- ☐ 1¼" nap rollers

Don't Forget the Accessories:

- | | |
|---|--|
| ☐ Gloves | ☐ Rags |
| ☐ Protective eyewear | ☐ Shoe covers |
| ☐ Soap and water (for cleanup) | ☐ Chip brushes |
| ☐ Masking tape & masking paper | ☐ Contractor-grade trash bags |



For additional information, contact GAF Design Services
at 1-877-423-7663 or designservices@gaf.com

We protect what matters most™

GAF