

Brai® Supreme™ Ply 4

Data Sheet



*Quality You Can Trust Since 1886...
From North America's Largest Roofing Manufacturer™*

Brai® Supreme™ - Ply 4

Technical Data Sheet

PRODUCT: Brai® Supreme™ Ply 4, glass fiber reinforced ply sheet; (formerly Tough Ply IV)

DESCRIPTION: Brai® Supreme™ Ply 4 is an extra strength, glass fiber reinforced ply sheet designed for use in climatic regions with the potential for high thermal shock. Compatible for use with built-up and modified asphalt roof systems. Brai® Supreme™ Ply 4 should not be used as a base sheet in any specification requiring mechanical attachment. Technical and sales information can be obtained through the U.S. Intec Technical Services Hotline, (800)-624-6832.

APPLICATION: Brai® Supreme™ Ply 4 is applied with hot roofing asphalt Type III or IV, or hot SEBS modified roofing asphalt Type III or IV.

APPROVALS: Brai® Supreme™ Ply 4 is listed and approved by the following agencies or code bodies: Underwriters Laboratories (UL), Type G1; Factory Mutual (FM). Conforms to or exceeds the tensile strength requirements of ASTM D 2178, Type IV.

PRODUCT DATA: Brai® Supreme™ Ply 4 (typical)

Weight 40 lb/roll (18.2 kg/roll)

Roll Dimensions 39 3/8" 1 m x 161.8 (49.3 m)

Roll Size 5 squares of roof area

Data Sheets

Data reported based on available independent and in-house resources. U.S. Intec reserves the right to change or modify, at its discretion, and without prior notice, any of the information, requirements, specifications or policies contained in this document.



1361 Alps Road
Wayne, NJ 07470
Technical Hotline (800) 624-6832
internet: www.usintec.com • email address: support@usintec.com