

# Brai® Supreme™ Ply 6 Glass Ply Sheet

## Data Sheet



*Quality You Can Trust Since 1886...  
From North America's Largest Roofing Manufacturer™*

# Brai® Supreme™ - Ply 6 Glass Ply Sheet

## Technical Data Sheet

**PRODUCT:** Brai® Supreme™ - Ply 6, glass fiber reinforced ply sheet; (formerly Ultra Ply VI)

**DESCRIPTION:** Brai® Supreme™ - Ply 6 is a superior, glass fiber reinforced ply sheet designed for use in temperate climate regions with the potential for high thermal shock. Compatible for use with built-up and modified asphalt roof systems. May be installed with hot roofing asphalt Type III or IV, or hot SEBS modified roofing asphalt Type III or IV. Brai® Supreme™ - Ply 6 Glass Ply Sheet should not be used as a base sheet in any specification requiring mechanical attachment. Technical and sales information can be obtained through the US Intec Technical Services Hotline, (800)-624-6832.

**APPLICATION:** Brai® Supreme™ - Ply 6 Glass Ply Sheets applied with hot roofing asphalt Type III or IV, or hot SEBS modified.

**APPROVALS:** Brai® Supreme™ - Ply 6 Glass Ply Sheets listed and approved by the following agencies or code bodies: Underwriters Laboratories (UL), Type G1; Factory Mutual (FM). Conforms to or exceeds the requirements of ASTM D 2178, Type VI.

**PRODUCT DATA:** Brai® Supreme™ - Ply 6 Glass Ply Sheet (typical)

Weight . . . . . 44 lb (20 kg) per roll  
Roll Dimensions . . . . . 39 3/8" (1 m) x 161.8' (49.3 m)  
Roll Size . . . . . 5 squares of roof area

Data Sheets

Data reported based on available independent and in-house resources. U.S. Intec reserves the right to change or modify, at its discretion, and without prior notice, any of the information, requirements, specifications or policies contained in this document.



1361 Alps Road  
Wayne, NJ 07470  
Technical Hotline (800) 624-6832  
internet: [www.usintec.com](http://www.usintec.com) • email address: [support@usintec.com](mailto:support@usintec.com)