

# Brai® Supreme™ Eliminator™ Nailable

## Data Sheet



*Quality You Can Trust Since 1886...  
From North America's Largest Roofing Manufacturer™*

# Brai<sup>®</sup> Supreme<sup>™</sup> Eliminator<sup>™</sup> - Nailable

## Technical Data Sheet

**PRODUCT:** Brai Supreme Eliminator Nailable, granule surfaced, glass fiber reinforced base sheet (formerly Permavent<sup>®</sup>)

**DESCRIPTION:** Brai Supreme Eliminator Nailable is a heavy weight, glass fiber reinforced base sheet with the bottom of the sheet granule-surfaced to provide positive venting of trapped gases under the roof membrane. Compatible for use with built-up and modified asphalt roof systems. May be mechanically attached to nailable decks. Technical and sales information can be obtained through the U.S. Intec Technical Services Hotline, (800) 624-6832.

**APPLICATION:** Brai Supreme Eliminator Nailable is mechanically attached.

**APPROVALS:** Brai Supreme Eliminator Nailable is listed and approved by the following agencies or code bodies: Underwriters Laboratories (UL), Type G2; Factory Mutual (FM). Conforms to or exceeds the requirements of ASTM D4897, Type I/II.

**PRODUCT DATA:** Brai Supreme Eliminator Nailable (typical)

Weight . . . . . 82 lb (37 kg) per roll  
Dimensions . . . . . 39 3/8" x 40'8" (1 m x 12.4 m)  
Roll Size . . . . . 1.25 square of roof area

Data Sheets

Data reported based on available independent and in-house resources. U.S. Intec reserves the right to change or modify, at its discretion, and without prior notice, any of the information, requirements, specifications or policies contained in this document.



1361 Alps Road  
Wayne, NJ 07470  
Technical Hotline (800) 624-6832  
internet: [www.usintec.com](http://www.usintec.com) • email address: [support@usintec.com](mailto:support@usintec.com)