

Brai® Supreme™ Eliminator™ Perforated

Data Sheet



*Quality You Can Trust Since 1886...
From North America's Largest Roofing Manufacturer™*

Brai® Supreme™ Eliminator™ - Perforated

Technical Data Sheet

PRODUCT: Brai Supreme Eliminator Perforated, granule surfaced, glass fiber reinforced venting base sheet

DESCRIPTION: Brai Supreme Eliminator Perforated is a heavy weight, glass fiber reinforced venting base sheet with the bottom of the sheet granule-surfaced to provide positive venting of trapped gases under the roof membrane. Compatible for use with built-up and hot applied, modified asphalt roof systems. Supreme Eliminator Perforated is spot adhered over suitable substrates. Technical and sales information can be obtained through the U.S. Intec Technical Services Hotline, (800) 624-6832.

APPLICATION: Brai Supreme Eliminator Perforated is laid out dry and then adhered with hot roofing asphalt Type III or IV, or hot SEBS modified roofing asphalt Type III or IV when subsequent plies are installed.

APPROVALS: Brai Supreme Eliminator Perforated is listed and approved by the following agencies or code bodies: Underwriters Laboratories (UL), Type G2; Factory Mutual (FM). Conforms to or exceeds the requirements of ASTM D4897, Type I/II.

PRODUCT DATA: Brai Supreme Eliminator Perforated (typical)

Weight 80 lb (36 kg) per roll

Dimensions 39 3/8" x 40'8" (1 m x 12.4 m)

Roll Size 1.25 squares of roof area

Data Sheets

Data reported based on available independent and in-house resources. U.S. Intec reserves the right to change or modify, at its discretion, and without prior notice, any of the information, requirements, specifications or policies contained in this document.



1361 Alps Road
Wayne, NJ 07470
Technical Hotline (800) 624-6832
internet: www.usintec.com • email address: support@usintec.com