



ROLL LEAD FLASHING 1" (25.4 mm)
DOWN INTO PIPE

PLUMBING VENT STACK

LIBERTY™ CAP SHEET TARGET SET IN
MATRIX™ 201 PREMIUM SBS FLASHING
CEMENT

PRIMED LEAD FLASHING, MINIMUM
2 1/2 - 4 LBS (1.13 - 1.81 KG). SET IN
MATRIX™ 201 PREMIUM SBS FLASHING
CEMENT

LIBERTY™ CAP SHEET FIELD
MEMBRANE

LIBERTY™ BASE SHEET(S)

ENERGYGUARD™ ROOF INSULATION

DECK

NOTE:

1. ONE PLY OF LIBERTY™ CAP SHEET SET IN A TROWELING OF MATRIX™ 201 PREMIUM SBS FLASHING CEMENT.
2. INSTALL LEAD FLASHING IN A SOLID BED OF MATRIX™ 201 PREMIUM SBS FLASHING CEMENT OVER THE COMPLETED LIBERTY™ FIELD MEMBRANE.
3. REFER TO LIBERTY™ FLASHING SPECIFICATIONS, PART 9.
4. LIBERTY™ FLASHING DETAILS FOR USE ON LIBERTY™ ROOFING SYSTEMS ONLY.



Liberty

ROOF
PENETRATION
SERIES

VENT STACK FLASHING DETAIL

DRAWING #
15

SYSTEM
LIB

SCALE
N.T.S.

ISSUE/ REVISION DATE
1-4-17