

TG-2[™]

SBS-Modified All-Purpose Underlayment/Base Sheet
Wrinkle-free underlayment/base sheet for tile, shingle, cedar and BUR.



Elk TG-2 is a fiberglass-reinforced SBS-modified underlayment designed for: tile, shingle, cedar and BUR roofing. It is also an ideal material as a base sheet for built-up systems. Elk TG-2 offers exceptional “wrinkle free” and “lay flat” properties. Elk TG-2 can be used in conjunction with UL approved low-slope applications. For technical information, contact 888.743.4527.

Plant Location:
3441 S. Willow Ave.
Fresno, CA 93725
559.499.2222

© 2006 Elk Premium Building Products, Inc. All rights reserved. All trademarks designated ® are registered trademarks and all trademarks designated ™ are other trademarks of Elk Premium Building Products, Inc., an ElkCorp company (NYSE:ELK), or its subsidiaries.

FEATURES:

- Manufactured with SBS-modified asphalt.
- Fiberglass-reinforced.
- Replaces conventional underlayment products.
- Exceptional “wrinkle free” and “lay flat” properties.
- Exceeds all physical properties of ASTM D226 for Type II felt.

HANDLING AND STORAGE:

- Store rolls in standing position only.
- Store in clean, dry, cool area.
- Do not store more than two pallets high. When storing two pallets high, place a sheet of plywood between pallets.
- Do not store directly in sunlight.

PACKAGING:

- Roll size:
36" x 72' (0.91 m x 21.95 m)
- Roll:
2 square (20.06 sq. m2)
- 25 rolls per pallet

APPROVALS:

- Class A approved under Class A fire-rated roofs (L26541).
- ICCES ER-5625
- FBC 2337
- IRC/IBC
- UL R21129



TG-2 SBS Modified All-Purpose Underlayment/Base Sheet

RECOMMENDED APPLICATION GUIDE

Slopes 4/12 and greater

- Install one layer of TG-2.
- Starting at the eaves, apply a 36" wide (0.91 m) sheet of underlayment overlapping successive sheets 2" (51 mm). Lay lines provided on product.
- All end laps must be a minimum of 6" (152.4 mm).
- Offset end laps 6' (1.82 m).
- Apply double coverage to all valleys, hips and ridges.
- Nail to hold in place. Do not use hammer tacks or staples.

Slopes between 2/12 and 4/12

- Install two layers of TG-2.
- Apply 19" (0.48 m) strip of underlayment parallel with and starting at the eaves.
- Starting at eaves, apply a 36" wide (0.91 m) sheet of underlayment overlapping successive sheets 19" (0.48 m).
- All end laps must be a minimum of 6" (152.4 mm).
- Offset end laps 6' (1.82 m).
- Nail to hold in place. Do not use hammer tacks or staples.

Application recommendations apply to asphalt composition shingle roofs only. For tile roofs, see applicable building codes or manufacturer's installation recommendations. Contact technical support, 888.743.4527, for low-slope roofing applications.

ASTM D4869
FOUR HOUR
SHOWER

ELK TG-2 APPROXIMATE MEASURES

Length	72'	21.9 m
Width	36"	0.91 m
Size	216 sq. ft.	20.1 sq. m

Notes:

- Ten lay lines
- Material should be unrolled, exposed to sunlight and allowed to relax prior to installation.

ELK TG2 - TECHNICAL DATA

PROPERTY	TEST METHOD	TYPICAL VALUE
Breaking Strength	ASTM D226	M.D. = 47 C.D. = 47
Loss on Heating	ASTM D146	0.3% Pass
Pliability @ 25°C	ASTM D4601-97a	Pass
Resistance to Liquid Transmission	ASTM D4869-88	Pass
Thickness of Membrane	ASTM D2626-97	Pass
Water Vapor Transmission	ASTM E96	0.03 Perms
Fire Test	ASTM E108	Pass

APPROVALS

Class A approved under Class A fire-rated composition roofs. (Warnock Hersey International L26541)
ICCER ER-5625, FBC 2337.14, IRC/IBC, UL R21129