

TOPCOAT® Liquid-Applied Roofing Systems

Flashing Fabric

(TOPGN160)

Updated: 7/14



*Quality You Can Trust...From
North America's Largest Roofing Manufacturer!™*

FLASHING FABRIC

Description

TOPCOAT[®] Flashing Fabric is a stitch bond, 100% polyester web that can be used in a variety of roofing installations and repairs. Flashing Fabric is designed for use with TOPCOAT[®] FlexSeal[™] Sealants and MajorSeal[™] Liquid Flashing at all penetrations, joints, or other areas that are subjected to high shear or stress.

Uses

TOPCOAT[®] Flashing Fabric is designed for reinforcing application and repairs made with TOPCOAT[®] FlexSeal[™] Sealants and MajorSeal[™] Liquid Flashing.

Advantages

- Lower cost on repairs compared to torched MB patches and metal patches

- One product fits most repairs
- Extremely flexible and durable
- Guarantees for full system repairs are available for up to 20 years*
- Standard sizes available: 4" x 300', 6" x 300', 12" x 300'. 20" x 300' rolls available as special order

For Application Questions

Contact GAF Technical Services at 1-800-766-3411 or visit gaf.com.

Note: Repair leaks promptly to avoid adverse effects, including mold growth.

**See applicable warranties and guarantees for complete coverage and restrictions.*

TOPCOAT[®] FLASHING FABRIC TECHNICAL DATA

Average Weight (ounces per square yard):	3.4
Average Tensile Strength per ASTM D5034:	74 lbs. warp; 45 lbs. weft
Average Elongation at break per ASTM D5034:	21.3% warp; 51.3% weft
Trapezoidal Tear Strength per ASTM D117:	13.5 lbs. warp; 24.2 weft
Thickness per ASTM D1777:	.018