

TOPCOAT® Liquid-Applied Roofing Systems

Sky-Lite

(TOPGN160)

Updated: 7/14



*Quality You Can Trust...From
North America's Largest Roofing Manufacturer!™*

TOPCOAT®

LIQUID-APPLIED ROOFING

SKY-LITE

Description

TOPCOAT® Sky-Lite is a clear, solvent-based synthetic rubber sealer designed to protect and waterproof porous, deteriorated fiberglass-reinforced skylight panels.

Uses

TOPCOAT® Sky-Lite is specially designed to seal and rebind fiberglass mat or fiber used in the construction of skylight panels in addition to weathered plastic skylights. TOPCOAT® Sky-Lite protects and reconditions translucent fiberglass skylight panels found on roofs and walls. DO NOT use to repair cracked or broken skylight panels. DO NOT apply at temperatures below 32°F. Substrate temperatures must be below 120°F when applying product.

Advantages

- Helps to seal out water and prevents leaking of porous skylight perimeters
- Seals and binds reinforcing fibers and extends the life of the skylight panels
- Reconditions leaky panels
- Assists in the restoration of original skylight clarity
- Limited material warranty available for up to 10 years*
- Available in 5-gallon pails

For Application Questions

Contact GAF Technical Services at 1-800-766-3411 or visit gaf.com.

Applicable Standards

ASTM D2196, ASTM D1475, ASTM E1644

Note: Repair leaks promptly to avoid adverse effects, including mold growth.

**See applicable warranties for complete coverage and restrictions.*

TOPCOAT® SKY-LITE TECHNICAL DATA

Application Rate:	1 gallon/100 sq. ft. per coat
Application Method:	Roller or brush
Application Temp (air, surface):	32° - 120°F
Drying Time (75°F, 50% RH):	Approximately 1 hour per coat
Wet Mil Thickness:	(1.0 Gallon/100SF) - 16 wet mils
Dry Mil Thickness:	(1.0 Gallon/100SF) - 6 dry mils
Total Solids (by weight):	40.2% ± 2%
Total Solids (by volume):	35% ± 2%
Specific Gravity:	0.91 ± 0.1
Weight per Gallon:	7.6 ± 0.5 lbs
Viscosity (75°F):	3,000 ± 400 cps
Storage:	Store in well-ventilated area at 50°F to 80°F; protect from freezing
Shelf Life:	1 year
Clean-Up:	Mineral Spirits, Toluene, Xylene

LEED® Credit
Available

State of
Florida
Approved

