

TopCoat® Topester Fabric

Information Sheet

Updated: 1/07



*Quality You Can Trust Since 1886...
From North America's Largest Roofing Manufacturer™*



TOPESTER FABRIC

Description

TOPESTER Fabric is a non-woven, 100% fully spun-bonded polyester web that can be used in all sorts of roofing installations and repairs. TOPESTER Fabric must be used in conjunction with TOPCOAT® Flashing Grade, SB-900 and FlexSeal at all penetrations, joints or other areas that are subjected to high shear or stress.

Uses

TOPESTER Fabric is designed for reinforcing repairs made with TOPCOAT® Flashing Grade, FlexSeal or SB-900.

Advantages

- Lower cost on repairs compared to torched MB patches, heat-sealed single ply patches and metal patches
- One product fits most repairs

- Extremely flexible and durable
- Durable and UV resistant; will not chalk, crack or peel
- Warranties for full system repairs are available for up to 10 years*
- Guarantees for full system repairs are available for up to 20 years*
- Available in 6"x150' and 12"x150' rolls

For application questions, please contact GAFMC Contractor Services at 1-800-766-3411.

Note: Repair leaks promptly to avoid adverse effects, including mold growth.

*See warranties and guarantees for complete coverage and restrictions.

TOPCOAT® TOPESTER FABRIC TECHNICAL DATA

Average Weight (Ounces per square yard) per ASTM D1117:	1.5
Average Tensile Strength per ASTM D1628:	44 psi
Average Elongation at break per ASTM 1628:	53%
Trapezoidal Tear Strength per ASTM D2263:	18.5 lbs
Storage:	Store in well-ventilated area at 50°F to 80°F; protect from freezing



For further information, contact GAF Contractor Services at: 1-800-766-3411 or visit www.gaf.com
©2007 GAF Materials Corporation 1/07