

GAFGLAS® #75 Base Sheet

Updated: 8/16



*Quality You Can Trust...From
North America's Largest Roofing Manufacturer!™*



GAFGLAS[®] #75 BASE SHEET

Description

GAFGLAS[®] #75 Base Sheet is a premium roofing base sheet constructed with a strong glass mat that is coated on both sides to ensure a closed-sheet design to prevent asphalt bleed-through. The sealed sheet also serves as an effective flame retarder for the application of torch-applied modified bitumen membranes.

Uses

GAFGLAS[®] #75 Base Sheet is engineered for use in the construction of GAFGLAS[®] built-up and RUBEROID[®] modified bitumen roofs. It is suitable for nailable specifications, such as plywood, where bleed-through is a concern.

Advantages

- Extra strength for excellent nail-holding ability. Superb tensile strength and resilience and no bleed through, thereby reducing risks of splitting and cracking of membrane.
- Will not rot, curl, or shrink; dimensionally stable for improved membrane performance.
- Designed to meet UL Class A ratings.
- Rolls out flat for easy installation.
- System guarantees are available for up to 20 years.*



Applicable Standards

| |
|--|
| Meets ASTM D4601, Type II |
| FM Approved |
| ICC ESR-1274 |
| Miami-Dade County Product Control Approved |
| UL/ULC Listed |

Product Specifications (nominal)

| | |
|---------------------|---|
| Roll Size | 3 squares (320.1 gross sq. ft.) (29.7 m ²) |
| Roll Length | 97.5' (29.7 m) |
| Roll Width | 39.375" (1.0 m) |
| Approx. Roll Weight | 68 lb (30.8 kg) |

* See applicable guarantee for complete coverage and restrictions.