

GAFGLAS[®] FlexPly[™] 6 Ply Sheet

Updated: 8/16



*Quality You Can Trust...From
North America's Largest Roofing Manufacturer!™*



GAFGLAS[®]

FLEXPLY[™] 6

PLY SHEET



Description

GAFGLAS[®] FlexPly[™] 6 Ply Sheet is a premium-performing fiberglass Type VI roofing felt. Its revolutionary flexible design provides:

- Maximum strength and stability.
- Improved conformance to underlying substrates.
- Ease of installation compared to typical Type VI felts.
- Long-term performance for peace of mind.

Uses

GAFGLAS[®] FlexPly[™] 6 Ply Sheet should be specified as a ply felt in the construction of all premium-quality built-up roofs, including:

- Most GAF Composite Roof[™] systems.
- Also appropriate for use as a base sheet and in the construction of flashing membranes.

Advantages

- System guarantees are available for up to 20 years.*
- Revolutionary flexible design—Rolls out easier and lies flatter, minimizing the danger of air pockets and trapped moisture during installation.
- Saves labor—Open pore design actively absorbs asphalt, installs faster than other Type VI felts.

Advantages (Continued)

- Quality installation—Enhanced porosity encourages proper absorption of asphalt for long-lasting system performance up to 20 years.*
- Proprietary Micro Weave[™] Core—Provides superior tensile strength and dimensional stability for greater resistance to splitting and cracking.
- Superior wind resistance—Selected systems have FM Class 1-180 rating.
- Highest fire rating—For use in UL, ULC Class A rated assemblies.
- Can be used in all climate zones.

Applicable Standards

Meets ASTM D2178, Type VI
FM Approved
ICC ESR-1274
Miami-Dade County Product Control Approved
State of Florida Approved
Texas Department of Insurance
UL/ULC Listed

Product Specifications (nominal)

Roll Size	5 squares (531 gross sq. ft.) (49.3 m ²)
Roll Length	161.8' (49.3 m)
Roll Width	39.375" (1.0 m)
Approx. Roll Weight	44 lb (20.0 kg)

* See applicable guarantee for complete coverage and restrictions.