



Metal Etch Primer

Safety Data Sheet 4005

Revision Date: 07/07/2016

Date of issue: 04/06/2016

Supersedes Date: 01/01/2005

Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Metal Etch Primer

1.2. Intended Use of the Product

Use of the substance/mixture: Corrosion resistance metal primer

1.3. Name, Address, and Telephone of the Responsible Party

Company

GAF
1 Campus Drive
Parsippany, NJ 07054 USA
1-800-766-3411

Emergency Number : CHEMTREC [DAY OR NIGHT] 1-800-424-9300
Outside USA and Canada: 1 703-741-5970

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US classification

Not classified

2.2. Label Elements

GHS-US Labeling

No labeling applicable

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions. This product contains a small amount of Crystalline Silica (Quartz) dust that is mixed with a liquid to form a primer mixture, and therefore the dust is not likely to be dispersed into the air. If the product is dried, dust is generated, and is released into the air; repeated exposure to respirable (airborne) Crystalline Silica (Quartz) dust may cause lung damage in the form of silicosis, lung cancer, or respiratory irritation.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	%	GHS-US classification
Pigment	(CAS No) Proprietary	10 - 45	Not classified
Colorant	(CAS No) Proprietary	2 - 8	Comb. Dust
Proprietary cosolvent	(CAS No) Proprietary	1 - 5	Flam. Liq. 4, H227 Eye Irrit. 2A, H319
Proprietary cosolvent 1	(CAS No) Proprietary	0.2 - 1.5	Not classified
Proprietary Cosolvent 3	(CAS No) Proprietary	0.1 - 0.35	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
Quartz	(CAS No) 14808-60-7	0.05 - 0.2	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372
Magnesium oxide (MgO)	(CAS No) 1309-48-4	< 0.1	Not classified
Butyl methacrylate	(CAS No) 97-88-1	< 0.1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Acute 3, H402

Metal Etch Primer

Safety Data Sheet 4005

Methacrylic acid	(CAS No) 79-41-4	< 0.1	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 3, H402
Anti-oxidant	(CAS No) Proprietary	0.0005 - 0.0010	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Viscosity modifier	(CAS No) Proprietary	< 0.001	Comb. Dust

Full text of H-phrases: see section 16

The specific chemical identity and/or exact percentage of composition has been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200]. In the event of an emergency, chemical identities and exact percentages of the proprietary ingredients may need to be disclosed to emergency personnel upon request.

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

First-aid Measures After Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/Injuries: Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/Injuries After Inhalation: Prolonged inhalation of vapors may cause respiratory irritation.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None known.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, dry chemical, foam, carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions closed containers may rupture or explode.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. Do not breathe fumes from fires or vapors from decomposition. Do not allow run-off from firefighting to enter drains or water courses.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid prolonged contact with eyes, skin and clothing. Avoid breathing (vapor, mist, spray).

6.1.1. For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Metal Etch Primer

Safety Data Sheet 4005

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. See Section 13, Disposal Considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing vapors, mist, and spray.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool and well-ventilated place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Protect from freezing.

Incompatible Products: Strong acids, strong bases, strong oxidizers. Acid anhydrides. Anhydrides. Water reactive materials.

Storage Temperature: 4 - 32 °C

7.3. Specific End Use(s)

Corrosion resistance metal primer

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Methacrylic acid (79-41-4)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	70 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	20 ppm
Proprietary cosolvent 1 (Proprietary)		
USA AIHA	WEEL TWA (mg/m ³)	10 mg/m ³
Proprietary Cosolvent 3 (Proprietary)		
USA ACGIH	ACGIH Ceiling (mg/m ³)	100 mg/m ³ (aerosol only)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
Proprietary cosolvent (Proprietary)		
USA ACGIH	ACGIH TWA (ppm)	10 ppm (inhalable fraction and vapor)
Colorant (Proprietary)		
USA ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ (respirable fraction)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³ (dust and fume)
USA IDLH	US IDLH (mg/m ³)	2500 mg/m ³ (dust and fume)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	10 mg/m ³ (fume) 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Pigment (Proprietary)		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)

Metal Etch Primer

Safety Data Sheet 4005

		5 mg/m ³ (respirable fraction)
Quartz (14808-60-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
USA ACGIH	ACGIH chemical category	A2 - Suspected Human Carcinogen
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³ (respirable dust)
USA IDLH	US IDLH (mg/m ³)	50 mg/m ³ (respirable dust)
USA OSHA	OSHA PEL (STEL) (mg/m ³)	250 mppcf/%SiO ₂ +5, 10mg/m ³ /%SiO ₂ +2
Viscosity modifier (Proprietary)		
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Magnesium oxide (MgO) (1309-48-4)		
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³ (inhalable fraction)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA IDLH	US IDLH (mg/m ³)	750 mg/m ³ (fume)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (fume, total particulate)
Anti-oxidant (Proprietary)		
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (inhalable fraction and vapor)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³

8.2. Exposure Controls

Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles.



Materials for Protective Clothing

: Chemically resistant materials and fabrics.

Hand Protection

: Wear protective gloves.

Eye Protection

: Chemical safety goggles.

Skin and Body Protection

: Wear suitable protective clothing.

Respiratory Protection

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Environmental Exposure Controls

: Avoid release to the environment.

Other Information

: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Red viscous liquid
Odor	: Mild acrylic/ammonia
Odor Threshold	: No data available
pH	: 9 - 9.5
Evaporation Rate	: < 1 (n-Butyl Acetate=1)
Melting Point	: No data available
Freezing Point	: ≈ 0 °C (32 °F)
Boiling Point	: ≈ 100 °C (212 °F)
Flash Point	: > 200 °F (> 93.33 °C) (PMCC)
Auto-ignition Temperature	: No data available

Metal Etch Primer

Safety Data Sheet 4005

Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20 °C	: Heavier than air
Relative Density	: No data available
Specific Gravity	: 1.27 - 1.29
Specific gravity / density	: 10.6 - 10.9 lb/gal
Solubility	: Miscible with water.
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: 2000 - 5000 cPs

9.2. Other Information No additional information available

SECTION 10: STABILITY AND REACTIVITY

- 10.1. **Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. **Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. **Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. **Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. **Incompatible Materials:** Strong acids, strong bases, strong oxidizers. Acid anhydrides. Anhydrides. Water reactive materials.
- 10.6. **Hazardous Decomposition Products:** Carbon oxides (CO, CO₂). Nitrogen oxides. Hydrocarbons. Metal oxides. Formaldehyde.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information On Toxicological Effects

Acute Toxicity: Not classified

Metal Etch Primer	
LD50 Oral Rat	3038 mg/kg
Butyl methacrylate (97-88-1)	
LD50 Oral Rat	16 g/kg
LD50 Dermal Rabbit	10181 mg/kg
LC50 Inhalation Rat	4910 ppm/4h
Methacrylic acid (79-41-4)	
LD50 Oral Rat	1060 mg/kg
LD50 Dermal Rabbit	500 - 1000 mg/kg
LC50 Inhalation Rat	7.1 mg/l/4h
ATE (Gases)	4,500.00 ppmV/4h
ATE (Dust/Mist)	1.50 mg/l/4h
Proprietary cosolvent 1 (Proprietary)	
LD50 Oral Rat	20 g/kg
LD50 Dermal Rabbit	20800 mg/kg
Proprietary Cosolvent 3 (Proprietary)	
LD50 Dermal Rat	10600 mg/kg
ATE (Oral)	500.00 mg/kg body weight
Proprietary cosolvent (Proprietary)	
LD50 Oral Rat	5660 mg/kg
LD50 Dermal Rabbit	2700 mg/kg
Colorant (Proprietary)	
LD50 Oral Rat	> 10000 mg/kg
Quartz (14808-60-7)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 5000 mg/kg
Viscosity modifier (Proprietary)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 5800 mg/m ³ (Exposure time: 4 h)

Metal Etch Primer

Safety Data Sheet 4005

Anti-oxidant (Proprietary)	
LD50 Oral Rat	> 2930 mg/kg (Species: Sprague-Dawley)
LD50 Dermal Rat	> 2000 mg/kg

Skin Corrosion/Irritation: Not classified

pH: 9 - 9.5

Serious Eye Damage/Irritation: Not classified

pH: 9 - 9.5

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified.

Colorant (Proprietary)	
IARC group	3
Quartz (14808-60-7)	
IARC group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Anti-oxidant (Proprietary)	
IARC group	3

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation. inhalation of vapors may cause respiratory irritation.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None known.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Not classified.

Butyl methacrylate (97-88-1)	
LC50 Fish 1	11 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	32 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Methacrylic acid (79-41-4)	
LC50 Fish 1	85 mg/l (Exposure Time: 96 h - Species: Oncorhynchus mykiss[flow-through])
ErC50 (algae)	14 mg/l
NOEC chronic crustacea	53 mg/l
Proprietary cosolvent 1 (Proprietary)	
LC50 Fish 1	51600 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	10000 mg/l (Exposure time: 24 h - Species: Daphnia magna)
LC 50 Fish 2	41 - 47 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
Proprietary Cosolvent 3 (Proprietary)	
LC50 Fish 1	41000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	14 - 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
Proprietary cosolvent (Proprietary)	
LC50 Fish 1	1300 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Anti-oxidant (Proprietary)	
EC50 Other Aquatic Organisms 2	0.43 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)

Metal Etch Primer

Safety Data Sheet 4005

12.2. Persistence and Degradability

Metal Etch Primer	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Metal Etch Primer	
Bioaccumulative Potential	Not established.
Butyl methacrylate (97-88-1)	
Log Pow	2.26
Methacrylic acid (79-41-4)	
Log Pow	0.93
Proprietary cosolvent 1 (Proprietary)	
BCF fish 1	< 1
Log Pow	-0.92
Proprietary Cosolvent 3 (Proprietary)	
Log Pow	-1.93
Proprietary cosolvent (Proprietary)	
BCF fish 1	(no bioconcentration expected)
Anti-oxidant (Proprietary)	
BCF fish 1	230 - 2500
Log Pow	4.17

12.4. Mobility in Soil No additional information available

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Ecology – Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT Not regulated for transport

14.2. In Accordance with IMDG Not regulated for transport

14.3. In Accordance with IATA Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1 US Federal Regulations

Butyl methacrylate (97-88-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Methacrylic acid (79-41-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Proprietary cosolvent 1 (Proprietary)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule
Proprietary Cosolvent 3 (Proprietary)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
EPA TSCA Regulatory Flag	Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule
SARA Section 313 - Emission Reporting	1.0 %
Proprietary cosolvent (Proprietary)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

Metal Etch Primer

Safety Data Sheet 4005

EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule
---------------------------------	--

Colorant (Proprietary)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

Pigment (Proprietary)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

Quartz (14808-60-7)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

Viscosity modifier (Proprietary)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

Magnesium oxide (MgO) (1309-48-4)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

Anti-oxidant (Proprietary)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2 US State Regulations

Proprietary Cosolvent 3 (Proprietary)	
U.S. - California - Proposition 65 - Developmental Toxicity	WARNING: This product contains chemicals known to the State of California to cause birth defects.

Quartz (14808-60-7)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.

Butyl methacrylate (97-88-1)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	

Methacrylic acid (79-41-4)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	

Proprietary cosolvent 1 (Proprietary)	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	

Proprietary Cosolvent 3 (Proprietary)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	

Colorant (Proprietary)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	

Pigment (Proprietary)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	

Quartz (14808-60-7)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	

Viscosity modifier (Proprietary)	
U.S. - Massachusetts - Right To Know List	

Metal Etch Primer

Safety Data Sheet 4005

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

Magnesium oxide (MgO) (1309-48-4)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

Anti-oxidant (Proprietary)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 07/07/2016

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1A	Carcinogenicity Category 1A
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
Skin Sens. 1B	Skin sensitization Category 1B
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H227	Combustible liquid
Comb. Dust	May form combustible dust concentrations in air
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H312	Harmful in contact with skin

Metal Etch Primer

Safety Data Sheet 4005

H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Disclaimer

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. GAF cannot anticipate all conditions under which this information and product, or the products of other manufacturers in combination with this product, may be used. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.

Revision Information

Conversion to GAF SDS.