



ADVANTAGES & BENEFITS

- Enhances adhesion to chalky surfaces
- Meets most VOC emissions and regulations to eliminate facility downtime during installation.
- Nontoxic formulation is safe to apply
- Easy application and cleanup
- No special equipment required to install

Recommended Uses:

- Surface Primer for all types of masonry (brick, block, stucco, and concrete).
- Surface Primer for old chalky paint

PRODUCT DESCRIPTION

SureBond Primer is a water-based acrylic primer used for sealing all types of masonry, metal and chalky surfaces.

PACKAGING & SHELF LIFE

2 gallon (7.6 liter) bucket

5 gallon (19 liter) pail

Shelf life 18 months if unopened containers stored between 40°F and 70°F.

PHYSICAL PROPERTIES

SUREBOND PRIMER	
Solids by Weight	25% (±2)
Solids by Volume	23% (±3)
Density	8.5 lbs/gal

VOC	>200 g/L
pH	9.2

APPLICATION INSTRUCTIONS

SURFACE PREPARATION: As a minimum, clean and prepare surfaces to receive waterproofing by removing all loose and flaking particles, grease and laitance with the use of a stiff bristle push broom and or washing. Care should be taken not to inject water into the substrate during washing. In some cases, additional drying time may be required after the cleaning process. New concrete should be allowed to cure for at least 28 days before applying **SureBond Primer**.

APPLICATION: **SureBond Primer** comes ready to use, however, it is recommended that the container be shaken

or stirred before application. Apply **SureBond Primer** by brush or roller to area to the recommended coverage rate. Allow to dry before proceeding with additional products.

COVERAGE: may vary due to porosity of substrate. The average surface will use 0.4 – 0.25 gal/100 ft².

Coated Brick	0.33 gal/100 ft ² (6.9 m ² /L)
Stucco	0.4 gal/100 ft ² (5.75 m ² /L)
Painted Surface	0.25 gal/100 ft ² (9.2 m ² /L)
Block	0.4 gal/100 ft ² (5.75 m ² /L)
Split-Faced Block	<0.5 gal/100 ft ² (<4.6 m ² /L)

LIMITATIONS & PRECAUTIONS

Do not apply **SureBond Primer** at temperatures below 50°F (10°C), or when there is possibility of temperatures falling below 32°F (0°C) within a 4-hour period after

application. **SureBond Primer** will freeze and become unusable at temperatures below 32°F (0°C). Do not ship or store unless protection from freezing is available.

SAFETY & HANDLING

For specific information regarding safe handling of this material please refer to the Safety Data Sheet (SDS).

CLEAN UP

Thoroughly rinse application equipment with clean water.

GAF

1 Campus Drive
Parsippany, NJ 07054
1-800-ROOF-411
gaf.com

GAF Liquid-Applied

January 2016, supersedes March 2014

For technical, system, and warranty information, visit gaf.com or call 1-800-766-3411.

See applicable warranties and guarantees for complete coverage and restrictions.