

# SAFETY DATA SHEET



## 1. Identification

**Product identifier** STREETBOND COLORANT STORMY BLUE

**Recommended use** Colorant.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufacturer**

**Company name** GAF  
1 Campus Drive  
Parsippany, NJ 07054 USA

**Telephone** 1-800-766-3411

**Emergency phone number** CHEMTREC [DAY OR NIGHT] 1-800-424-9300  
Within USA and CANADA 1-800-424-9300  
Outside USA and Canada: 1 703-741-5970

## 2. Hazard(s) identification

**Physical hazards** Not classified.

**Health hazards** Carcinogenicity Category 2

**Environmental hazards** Not classified.

**OSHA defined hazards** Not classified.

### Label elements



**Signal word** Warning

**Hazard statement** Suspected of causing cancer.

**Precautionary statement**

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.

**Response** If exposed or concerned: Get medical advice/attention.

**Storage** Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)** None known.

**Supplemental information** None.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Titanium Dioxide		13463-67-7	30 to <40

Chemical name	Common name and synonyms	CAS number	%
Carbon Black		1333-86-4	10 to <20
Propylene Glycol		57-55-6	5 to <10
Silicate		14807-96-6	1 to <5
PARAFFINIC PETROLEUM OIL		64742-54-7	0.1 to <1
Other components below reportable levels			40 to <50

#### 4. First-aid measures

<b>Inhalation</b>	Move to fresh air. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Wash off with soap and water. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Rinse with water. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth. Get medical attention if symptoms occur.
<b>Most important symptoms/effects, acute and delayed</b>	Direct contact with eyes may cause temporary irritation.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	<p>Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.</p> <p>Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.</p> <p>Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.</p>
<b>Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground.

#### 7. Handling and storage

<b>Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
--------------------------------------	--

**Conditions for safe storage, including any incompatibilities**

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Carbon Black (CAS 1333-86-4)	PEL	3.5 mg/m3	
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.

#### US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Silicate (CAS 14807-96-6)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Silicate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Carbon Black (CAS 1333-86-4)	TWA	0.1 mg/m3	
Silicate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.

#### US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value	Form
Propylene Glycol (CAS 57-55-6)	TWA	10 mg/m3	Aerosol.

### Biological limit values

No biological exposure limits noted for the ingredient(s).

### Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

If contact is likely, safety glasses with side shields are recommended.

#### Skin protection

##### Hand protection

For prolonged or repeated skin contact use suitable protective gloves.

##### Other

Wear suitable protective clothing.

#### Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

#### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

### General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

### Appearance

Physical state	Liquid.
Form	Liquid.
Color	Not available.

<b>Odor</b>	Not available.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	3349.4 °F (1843 °C) estimated
<b>Initial boiling point and boiling range</b>	4532 °F (2500 °C) estimated
<b>Flash point</b>	201.0 °F (93.9 °C) estimated
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	3049.59 hPa estimated
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Density</b>	13.93 lbs/gal
<b>Flammability class</b>	Combustible IIIB estimated
<b>Percent volatile</b>	58.85 %
<b>Specific gravity</b>	1.67
<b>VOC</b>	256.994608 g/l Regulatory estimated 2.14466 lbs/gal Regulatory estimated 140.896593 g/l Material estimated 1.175804 lbs/gal Material estimated

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Prolonged inhalation may be harmful.
<b>Skin contact</b>	No adverse effects due to skin contact are expected.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	Expected to be a low ingestion hazard.

**Symptoms related to the physical, chemical and toxicological characteristics** Direct contact with eyes may cause temporary irritation.

**Information on toxicological effects**

**Acute toxicity**

Components	Species	Test Results
Carbon Black (CAS 1333-86-4)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Rat	> 8000 mg/kg
Propylene Glycol (CAS 57-55-6)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Guinea pig	18.4 g/kg
	Mouse	23.9 g/kg
	Rabbit	18 g/kg
	Rat	30 g/kg

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

**Serious eye damage/eye irritation** Direct contact with eyes may cause temporary irritation.

**Respiratory or skin sensitization**

**Respiratory sensitization** Not available.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** Suspected of causing cancer.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

Carbon Black (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**US. National Toxicology Program (NTP) Report on Carcinogens**

PARAFFINIC PETROLEUM OIL (CAS 64742-54-7) Known To Be Human Carcinogen.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

**Specific target organ toxicity - single exposure** Not classified.

**Specific target organ toxicity - repeated exposure** Not classified.

**Aspiration hazard** Not available.

**Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

**12. Ecological information**

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Propylene Glycol (CAS 57-55-6)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna) > 10000 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 710 mg/l, 96 hours

Components	Species	Test Results
Titanium Dioxide (CAS 13463-67-7)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna) > 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus) > 1000 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential**

**Partition coefficient n-octanol / water (log Kow)**

Propylene Glycol -0.92

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**13. Disposal considerations**

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

**14. Transport information**

**DOT**

Not regulated as dangerous goods.

**IATA**

Not regulated as dangerous goods.

**IMDG**

Not regulated as dangerous goods.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.

**15. Regulatory information**

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories** Immediate Hazard - No  
 Delayed Hazard - Yes  
 Fire Hazard - No  
 Pressure Hazard - No  
 Reactivity Hazard - No

**SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** No**SARA 313 (TRI reporting)**

Not regulated.

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.**US state regulations****US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**Carbon Black (CAS 1333-86-4)  
PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)  
Silicate (CAS 14807-96-6)  
Titanium Dioxide (CAS 13463-67-7)**US. Massachusetts RTK - Substance List**Carbon Black (CAS 1333-86-4)  
Silicate (CAS 14807-96-6)  
Titanium Dioxide (CAS 13463-67-7)**US. New Jersey Worker and Community Right-to-Know Act**Carbon Black (CAS 1333-86-4)  
Propylene Glycol (CAS 57-55-6)  
Silicate (CAS 14807-96-6)  
Titanium Dioxide (CAS 13463-67-7)**US. Pennsylvania Worker and Community Right-to-Know Law**Carbon Black (CAS 1333-86-4)  
Propylene Glycol (CAS 57-55-6)  
Silicate (CAS 14807-96-6)  
Titanium Dioxide (CAS 13463-67-7)**US. Rhode Island RTK**

Not regulated.

**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**Carbon Black (CAS 1333-86-4) Listed: February 21, 2003  
Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

<b>Issue date</b>	12-04-2014
<b>Revision date</b>	07-08-2016
<b>Version #</b>	05
<b>HMIS® ratings</b>	Health: 1* Flammability: 0 Physical hazard: 0
<b>NFPA ratings</b>	Health: 0 Flammability: 0 Instability: 0
<b>Disclaimer</b>	This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. GAF cannot anticipate all conditions under which this information and product, or the products of other manufacturers in combination with this product, may be used. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.
<b>Revision Information</b>	Product and Company Identification: Converted to GAF SDS