



SINGLE-PLY: TPO & PVC 60-80 mil membranes

EVERGUARD® TPO UTILITY FLASHING MEMBRANE (TPO ONLY) OR MIN. 8" (203 mm) WIDE REINFORCED EVERGUARD® MEMBRANE

REINFORCED EVERGUARD® MEMBRANE

HEAT WELD BOTH SIDES

WOOD NAILER MIN 2" X 1/2"

EVERGUARD® COATED METAL EDGE, SEE NOTE 1

EVERGUARD® WATER BLOCK

ROOF DECK/SUBSTRATE

MULTIPLE LAYERS OF ENERGYGUARD™ ROOF INSULATION, STAGGERED AND OFFSET

FOAM FILLED POCKET MIN. 1" (25.4 mm) OR AS SPECIFIED

SHEET METAL GUTTER

WALL

NOTE:

1. METAL EDGE SHOULD BE DESIGNED FOR WIND RESISTANCE IN ACCORDANCE WITH THE APPLICABLE EDITION OF ASCE 7 AND TESTED FOR CAPACITY IN ACCORDANCE WITH THE TEST METHODS IN THE APPLICABLE EDITION OF ANSI/SPRI ES-1.
2. FOR STEEL ROOF DECKS: FILL STEEL DECK FLUTES WITH SPRAY FOAM INSULATION PRIOR TO THE INSTALLATION OF ABOVE DECK INSULATION A MINIMUM OF 12 INCHES (305 mm) FROM FACE OF WALL.



GUTTER WITH COATED METAL ROOF EDGE

LEGEND

DRAWING #

211B

THIS DETAIL APPLIES TO:
ADHERED SYSTEMS
MECHANICALLY ATTACHED SYSTEMS
RHINOBOND® SYSTEMS

ISSUE / REVISION DATE

3/1/21

SCALE

N.T.S.

HEAT-WELDED

FLEXSEAL™ CAULK-GRADE SEALANT