



EVERGUARD® PVC

PVC Bonding Adhesive

Description

EverGuard® PVC Quick Lay Adhesive is a one-sided, wet lay-in, water-based adhesive useful for bonding smooth EverGuard® PVC membranes to various substrates.

- Suitable for roofing and flashing membranes
- Compatible with polyiso and fiber board, insulations, and fiberglass-faced gypsum panels
- Up to 50% faster installation than traditional bonding adhesives

Application

- Substrate surface should be dry, clean, and free from oil, grease, and other contaminants.
- Stir the adhesive thoroughly before use, either manually or by means of powered mixing equipment.
- Apply the adhesive evenly to the substrate only, avoiding puddles.
- Do not apply the adhesive in lap areas, as this will prevent proper heat welding.
- For smooth membrane - Using a standard roller, apply adhesive at 100-120 sq. ft. per gallon (2.45 - 2.94 m² per liter) to the roof substrate surface ONLY; approximately 600 sq. ft. (6 sqs) of installed membrane per pail.



- Install membrane immediately onto wet adhesive: do NOT allow adhesive to dry. Roll membrane onto the substrate surface and broom the membrane to ensure close contact between the membrane and the substrate surface.
- Not for use with EverGuard® PVC KEE or EverGuard® PVC XK Membranes.

See published application and specifications manual for detailed instructions.

PHYSICAL PROPERTIES

Weight per gallon:	8.5 lb./g (1 kg/L)
Viscosity:	10,000 cps
Solids content %:	65.5% +/- 1.5%
VOC:	<50 g/L
Storage:	Keep from freezing; store above 40°F (4.4°C)
Installation temperature:	Minimum application temperature is 40°F (4.4°C) and rising

Quality You Can Trust... From North America's Largest Roofing Manufacturer!™