



**GAF**

# EVERGUARD® TPO

## Description

EverGuard® TPO Quick Spray Adhesive and EverGuard® TPO Quick Spray Adhesive LV50 are sprayable, solvent-based contact adhesives useful for bonding smooth EverGuard® and EverGuard Extreme® TPO membranes to various substrates.

## Features and Benefits

- Up to 10 squares (93 square meters) of coverage per canister
- Faster installation than traditional bonding adhesive
- High initial tack

## Application:

- Substrate should be dry, clean, and free from oil, grease, and other contaminants
- Spraying from 8"–12" (203 – 305 mm) away, apply adhesive uniformly to both the substrate and the underside of the membrane
- Allow adhesive to dry to a tacky feel before bonding membrane to substrate
- Apply pressure with a push broom or weighted roller to ensure complete bonding



Refer to UL Online Certification Directory for actual assemblies.



## EverGuard® TPO Quick Spray Adhesive

### EverGuard® TPO Quick Spray Adhesive

**Item Number:** 7792

**VOC:** 489 g/L

**Shelf Life:** 1 year

**Installation Temperature:** 40° F (4.4° C) and rising

**Canister Weight:** 40.15 lb. (18.2 kg)

**Adhesive Weight:** 30 lb. (13.6 kg)

**Cleaner SKU:** 7802

**Hose & Gun SKU:** 7804

### EverGuard® TPO Quick Spray Adhesive LV50

**Item Number:** 7801

**VOC:** <80 g/L

**Shelf Life:** 1 year

**Installation Temperature:** 40° F (4.4° C) and rising

**Canister Weight:** 36.3 lb. (16.5 kg)

**Adhesive Weight:** 27 lb. (12.25 kg)

**Cleaner SKU:** 7803

**Hose & Gun SKU:** 7805

TPO Adhesive

We  
protect  
what  
matters  
most™

[gaf.com](http://gaf.com)