



EVERGUARD® TPO

TPO Accessories

Description

EverGuard® Liquid Flashing is designed to be applied in conjunction with flashing fabric and EverGuard® Base Coat to waterproof difficult flashing conditions on TPO membrane roof systems. Not for use in ponding water conditions or around drains or scuppers.

Application

- Membrane must be primed with EverGuard® Base Coat prior to applying EverGuard® Liquid Flashing.
- Fill any gaps ¼" (6 mm) up to ½" (13 mm) with M-Bond™ Adhesive/Sealant prior to installation.
- Install a base coat of liquid flashing to a 30 wet mil thickness using a notched trowel or a China bristle brush.
- Embed precut pieces of flashing fabric into the first coat of the liquid membrane so they extend a minimum of 4" (102 mm) onto the field membrane and 4" (102 mm) up the penetration. Use a notched trowel or a China bristle brush to work the fabric into the first coat of the liquid flashing so it lies smooth and flat.
- Install the second coat of EverGuard® Liquid Flashing to a thickness of 30 wet mils, working the liquid flashing completely over the fabric and extending a minimum of 2" (51 mm) past the end of the fabric.
- Complete the flashing by applying 2 coats of United Coatings™ Roof Mate™ Coating.



EverGuard® Liquid Flashing

SPECIFICATIONS	
EverGuard® Liquid Flashing Kit	Product SKU: 4252
Contains:	3 – 0.53-gallon (2 liter) pouches of EverGuard® Liquid Flashing
	2 – 2 – 10.1-oz. (300 ml) tubes M-Bond™ Sealant
	1 – Pair rubber gloves
	1 – Notched trowel
	3 – Nozzle extensions
	1 – 50' (15.24 m) roll of flashing fabric
EverGuard® Liquid Flashing 4-Pack	Product SKU: 801A
Contains:	4 – 0.53-gallon (2 liter) pouches of EverGuard® Liquid Flashing

Quality You Can Trust...From North America's Largest Roofing Manufacturer!™