

EverGuard® Separation Sheets

Information Sheet



*Quality You Can Trust Since 1886...
From North America's Largest Roofing Manufacturer™*

Product Data Sheet EverGuard® Separation Sheets

Description

GAF EverGuard® single-ply roofing systems include a full line of EverGuard separation sheets, both non-woven polyester (beige in color) and fiberglass fire-resistant (green in color) mat. EverGuard separation sheets are easy to install; loose applied sheets require little or no mechanical attachment. They protect the EverGuard membrane from damage, in the case of non-woven polyester sheets, and improve the overall fire resistance of roof assemblies, in the case of fiberglass sheets. The following EverGuard non-woven polyester sheets and fiberglass sheets are available:

Product	Description	Benefit/Application	Quantity/Size	Weight
Fiberglass Fire Sheet 10	Fire-resistant fiberglass mat	<ul style="list-style-type: none"> • Separation sheet installed over polystyrene foam insulation beneath mechanically attached and ballast applied membranes to obtain certain fire ratings • Separation sheet installed beneath insulation over wood decks to obtain certain fire ratings 	4' X 250'/roll	80 lbs./roll
Fiberglass Fire Sheet 50	Fire-resistant fiberglass mat	<ul style="list-style-type: none"> • Separation sheet installed beneath mechanically attached and ballast applied membranes over wood decks to obtain certain fire ratings • Separation sheet installed beneath insulation over wood decks to obtain certain fire ratings 	4' X 105'/roll	79 lbs./pail
Polymat Separation Layer 3 oz.	Non-woven polyester UV-stabilized mat, 3 oz/sq. yd.	<ul style="list-style-type: none"> • Separation sheet installed beneath mechanically attached and ballast applied membranes to protect from smooth surfaced substrates • Separation sheet installed over ballast applied membranes to protect from sharp edges of crushed or reused stone ballast, and beneath lightweight interlocking concrete pavers 	10' X 492'/roll	116 lbs./roll
Polymat Cushioning Layer 6 oz.	Non-woven polyester UV-stabilized mat, 6 oz/sq. yd.	<ul style="list-style-type: none"> • Separation sheet installed beneath mechanically attached or ballast applied membranes to protect from granule surfaced, rough and irregular surfaced substrates • Separation sheet installed over ballast applied membranes beneath standard non-interlocking concrete pavers 	10' X 328'/roll	125 lbs./roll

Note: Store separation materials in original rolls on pallets or shelving in a dry area. Mass and dimensions stated are nominal unless otherwise indicated.