

EverGuard® TPO GAF Yellow Safety Tape



Description:

EverGuard® TPO Yellow Safety Tape helps make a roof safer for everyone who needs to access it. It provides a highly visible warning to take caution around a variety of potential hazards:

- Edges
- Skylights
- Expansion joints
- Solar panels
- Other rooftop features

EverGuard® TPO Yellow Safety Tape is easy to install and lasts for years while requiring less maintenance than many paint coatings that perform the same function.

Application:

Clean the entire surface to be covered with soap and water, and dry thoroughly. Wipe the area to be primed with a white cloth moistened with EverGuard® TPO Seam Cleaner. Apply EverGuard® TPO Primer on surfaces mating with the butyl tape — only on the surfaces receiving the tape. After the primer has dried, pull a portion of the release paper on the back of the tape, exposing the butyl adhesive, and mate the two surfaces. Roll the tape portion of the cover strip at a 45-degree angle to ensure a good bond.*

* See EverGuard® Application and Specifications Manual for detailed application instructions and additional information on Yellow Safety Tape and Cover Tape.

Product Information:

EverGuard® TPO Yellow Safety Tape is a 6"- (152 mm) wide by 100'- (30.48 m) long cover tape made from nominal 30 mil unreinforced TPO. It can be used in conjunction with EverGuard® Yellow Walkway Rolls.

Also Available:



SPECIFICATIONS	
Width	6" (152 mm)
Length	100' (30.48 m)
SHIPPING SPECIFICATIONS	
Qty per box	2
Weight per box	38 lb. / 17.24 kg
Boxes per pallet	36
PRODUCT SKU	
TPO Yellow Safety Tape	755F902



Visit [gaf.com](https://www.gaf.com)

For additional information, contact GAF Technical Support at **1-800-766-3411** or technicalquestions@gaf.com

We protect what matters most™

