

EverGuard® TPO GAF Primer



Description:

EverGuard® TPO Primer and EverGuard® TPO Low VOC Primer are vital to surface preparation. Rely on GAF EverGuard® Primer and Low VOC Primer to help prepare metal and membrane for application of cover tape, and to help prepare membrane and pourable sealer pockets to apply EverGuard® One-Part Pourable Sealant.

Temperature:

Apply the primer at an ambient air temperature of 40° F (4° C) and rising.

Storage and Handling:

When not in use, ensure covers are securely in place. Store primers in a clean, well-ventilated space at 40° F (4° C) – 90° F (32.2° C). Improper sealing or storage for continued periods outside of this temperature range may shorten shelf life.

Shelf Life:

Primer shelf life is 12 months (18 months for Low VOC) from date of manufacture if unopened and properly stored.

Application:

Cover Tape

When installing cover tape, apply the primer with a 3" roller to both the metal and membrane. Allow the primer to flash off before applying the tape.

HW Cover Tape

When installing heat weld cover tape, apply the primer with a 3" roller to the metal only. Allow the primer to flash off before applying heat weld cover tape.

Pourable Sealant Pocket

Prior to filling the TPO Pourable Sealant Pocket, you must prime all areas that the one-part pourable sealant will come in contact with.

Codes and Compliance

- Miami-Dade County Product Control Approved



SPECIFICATIONS	TPO Primer	Low VOC TPO Primer*
Can size	1 gallon	1 gallon
Cans per carton	6	6
Coverage Rates	200 – 250 sq. ft. per gallon (18.6 – 23.2 m ² per liter)	200 – 225 sq. ft. per gallon (18.6 – 20.9 m ² per liter)
Product SKUs	755B	755D

* Maximum VOC <250g/L



Visit gaf.com

For additional information, contact GAF Technical Support at **1-877-423-7663** or designservices@gaf.com

We protect what matters most™

