

North America's #1-selling shingle just got better — again

With GAF time-release algaefighting technology and LayerLock® technology, Timberline HDZ® offers everything you can expect from an architectural shingle roof, and more.



Timberline HDZ® Shingles

Benefits:

- LayerLock® technology mechanically fuses the common bond between overlapping shingle layers
- Up to 99.9% nailing accuracy the StrikeZone® nailing area is so easy to hit that a roofer placed 999 out of 1,000 nails correctly in our test¹
- WindProven[™] Limited Wind Warranty — when installed with the required combination of GAF accessories, Timberline HDZ[®] shingles are eligible for a wind warranty with no maximum wind speed limitation²
- Dura Grip[™] sealant pairs with the microgranule surface of the StrikeZone[®] nailing area, and an

- asphalt-to-asphalt bond cures for durability, strength, and exceptional wind-uplift performance
- Great value architecturally stylish but practically priced, with a Lifetime[†] Limited Warranty
- 25-year StainGuard Plus™ Algae Protection Limited Warranty against blue-green algae discoloration³, thanks to our proprietary time-release algae-fighting technology that helps protect your shingles from unsightly stains
- For the best look use TimberTex® premium ridge cap shingles or TimberCrest® premium SBS-modified ridge cap shingles

Product details:

Product/System Specifics

- Fiberglass asphalt construction
- **Dimensions (approx.):** 13 1/4" x 39 3/8" (337 mm x 1,000 mm)
- **Exposure:** 5 %" (143 mm)
- Bundles/Square: 3
- Pieces/Square: 64
- StainGuard Plus™ Algae Protection Limited Warranty³
- Hip/Ridge: TimberTex®; TimberCrest®; Seal-A-Ridge®; Ridglass®
- Starter: Pro-Start®; QuickStart®; WeatherBlocker™

Applicable Standards & Protocols

- Passes UL 2218 Impact-Resistance Test with Class 3 rating
- UL Listed to ANSI/UL 790 Class A
- Classified by UL in accordance with ICC-ES AC438
- Meets ASTM D7158, Class H
- Meets ASTM D3161, Class F
- Meets ASTM D3018 Type 1
- Meets ASTM D3462⁴
- ICC-ES Evaluation Reports ESR-1475 and ESR-3267
- Meets CSA A123.5
- CAN/ULC-S107 Class A Roofing Fire Rating
- t Lifetime refers to the length of warranty coverage provided and means as long as the original individual owner(s) of a single-family detached residence [or eligible second owner(s)] owns the property where the qualifying GAF products are installed. For other owners/structures, Lifetime coverage is not applicable. Lifetime coverage on shingles requires the use of GAF Lifetime shingles only. See the GAF Shingle & Accessory Limitled Warnarly for complete coverage and restrictions. Visit gaf.com/LRS for qualifying GAF products. Lifetime coverage on shingles and accessories requires the use of any GAF Lifetime shingle and at least 3 qualifying GAF accessories. See the GAF Roofing System Limited Warnarly for complete coverage and restrictions. For installations not eligible for the GAF Roofing System Limited Warnarly, see the GAF Shingle & Accessory Limited Warnarly, Visit gaf.com/LRS for qualifying GAF products.
- Results based on study conducted by Home Innovation Research Labs, an independent research lab, comparing installation of Timberline HD® Shingles to Timberline HDZ® Shingles on a 16-square roof deck using standard 4-nail nailing pattern under controlled laboratory conditions. Actual results may vary.
- ² 15-year WindProven™ Limited Wind Warranty on GAF shingles with LayerLock® technology requires the use of GAF starter strips, roof deck protection, ridge cap shingles, and leak barrier or aftic ventilation. See GAF Roofing System Limited Warranty for complete coverage and restrictions. Visit gaf.com/LRS for qualifying GAF products. For installations not eligible for the GAF WindProven™ Limited Wind Warranty, see the GAF Shingle & Accessory Limited Warranty.
- ³ 25-year StainGuard Plus™ Algae Protection Limited Warranty against bluegreen algae discoloration is available only on products sold in packages bearing the StainGuard Plus™ logo. See GAF Shingle & Accessory Limited Warranty for complete coverage and restrictions, and qualifying products.
- ⁴ Periodically tested by independent and internal labs to ensure compliance with ASTM D3462 at time of manufacture.

Colors:







