



EnergyGuard™ NH Barrier Polyiso Insulation

GAF

Final Assembly: Cedar City, Utah, USA; Statesboro, Georgia, USA; Gainesville, Texas, USA

Life Expectancy: 25 Year(s)

End of Life Options: Salvageable/Reusable in its Entirety, Recyclable, Landfill

Ingredients:

Facer: Limestone; Acrylic Polymer; Glass Fiber; **Foam:** Polyisocyanurate Foam; **Blowing Agent:** Iso-Pentane; n-Pentane; **Catalyst 1:** Hexanoic acid, 2-ethyl-, potassium salt; **Catalyst 2:** Potassium Acetate; **Catalyst 3:** Pentamethyldiethylenetriamine; **Surfactant:** 1,2-Propanediol, Polymer with Ethyloxirane and Oxirane, Potassium Salt; **Proprietary:** Undisclosed (< 1%)¹

¹LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

☐ LBC Red List Free

☒ LBC Red List Approved

☐ Declared

% Disclosed: 99% at 100ppm

VOC Content: Not Applicable

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

GAF-0007

EXP. 01 AUG 2026

Original Issue Date: 2018

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY

INTERNATIONAL LIVING FUTURE INSTITUTE™ living-future.org/declare