



EnergyGuard™ NH HD Plus Polyiso GAF

Final Assembly: Multiple locations in the USA

Life Expectancy: 25 Year(s)

End of Life Options: Salvageable/Reusable in its Entirety,
Recyclable, Landfill

Ingredients:

Facer: Limestone; Acrylic Polymer; Glass Fiber; **Foam:** Polyisocyanurate Foam; **Blowing Agent:** Iso-Pentane; n-Pentane; **Catalyst 1:** Hexanoic acid, 2-ethyl-, potassium salt; **Catalyst 2:** Potassium Acetate; **Catalyst 3:** Pentamethyldiethylenetriamine; **Surfactant:** 1,2-Propanediol, Polymer with Ethyloxirane and Oxirane, Potassium Salt

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

GAF-0005

EXP. 01 AUG 2026

Original Issue Date: 2017