



EnergyGuard™ NH Ultra Polyiso Insulation GAF

Final Assembly: Multiple Locations in the USA

Life Expectancy: 25 Year(s)

End of Life Options: Salvageable/Reusable in its Entirety

Ingredients:

Facer: Limestone; Glass Fiber; Acrylic Polymer; **Foam:** Polyisocyanurate Foam; **Blowing Agent:** Iso-Pentane; n-Pentane; **Catalyst 1:** Hexanoic acid, 2-ethyl-, potassium salt; **Catalyst 2:** Potassium Acetate; **Catalyst 3:** Pentamethyldiethylenetriamine; **Surfactant:** 1,2-Propanediol, Polymer with Ethyloxirane and Oxirane, Potassium Salt; **Proprietary:** Undisclosed (< 1%)¹

¹LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| ☐ LBC Red List Free | % Disclosed: 99% at 100ppm |
| ☒ LBC Red List Approved | VOC Content: Not Applicable |
| ☐ Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

GAF-0003

EXP. 01 AUG 2027

Original Issue Date: 2017

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY

INTERNATIONAL LIVING FUTURE INSTITUTE™ living-future.org/declare