



EverGuard® SA TPO Self-Adhered Roof Membrane

GAF

Final Assembly: Mt. Vernon, Indiana, USA

Life Expectancy: 20 Year(s)

End of Life Options: Salvageable/Reusable in its Entirety

Ingredients:

Ethylene/Propylene Copolymer; Magnesium hydroxide; 1,3-Pentadiene, polymer with 2-methyl-2-butene; 1,3-Propandiamin, N,N''-1,2-ethandiylbis-, Polymer mit 2,4,6-trichlor-1,3-5-triazin, Reaktionsprodukt mit N-butyl-2,2,6,6-tetramethyl-4-piperidinamin; Benzene, ethenyl-, polymer with 2-methyl-1,3-butadiene; Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl) -4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester; Decanedioic acid, bis(2,2,6,6-tetramethyl-4-piperidiny) ester; Docosanamide; Octadecanoic acid, calcium salt; Octadecanoic acid, magnesium salt; Polyethylene Terephthalate; Titanium dioxide; Tris(2,4-di-tert-butylphenyl) phosphite; Undisclosed (< 1%)¹

¹LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| ☐ LBC Red List Free | % Disclosed: 99% at 100ppm |
| ☒ LBC Red List Approved | VOC Content: Not Applicable |
| ☐ Declared | |

I-10 Interior Performance: Not Applicable

I-14 Responsible Sourcing: Not Applicable

GAF-0010

EXP. 01 AUG 2027

Original Issue Date: 2023