



We
protect
what
matters
most™

Technical Advisory Bulletin

To: GAF Commercial Sales, GAF Contractors, Field Services, AIS, CARE

From: Technical Services Department

No: TAB-C-04

Energy Saving Coatings for GAF APP & SBS Membranes

*May I Coat My
GAF Warranted
Roof For Energy
Savings?*

Yes... GAF has several CRRC rated products available to help you meet your energy savings goals. They are designed to be chemically and physically compatible with our APP and SBS roofing systems and carry some of the best limited warranties in the industry.

The GAF recommended products are:

- **United Coatings™ Roof Mate MB Plus Coating**
- **United Coatings™ Surface Seal SB Roof Coating**

*Application
Recommend-
ations:*

Generally...

- The surface must be free of water, ice, snow and debris prior to application.
- Do not apply at temperatures below 42°F (5.5°C). Substrate temperatures must be below 140°F (60°C) when applying product.
- Allow new roofs to age for 90 days, clean existing roofs.
- The application rate will be approximately ½ - 1 gallon per 100sq. ft. depending on the product.
- The application can be by brush, roller or airless sprayer.
- Drying Time (75°F, 50% RH) is approximately 24 hours.

Before Application:



After Application:



Questions?

GAF Technical Services Can Assist You... with these and other questions you may have regarding your new roof installation. Technical Support Services can be contacted at 800-766-3411. The GAF website is a great resource for just about any question you may have or for additional information you may require. Please visit www.gaf.com to find the latest information on our products and their installation.

Important: This document supersedes any prior GAF Technical Advisory Bulletins on this topic. Please always check www.gaf.com to make sure you have the most up to date information.